

Luminaire

Code T081410
Name CICLOPE terra 90 bilaterale 6W 3000K ruggine

Measurement

Code FTS0000978
Name CICLOPE terra 90 bilaterale 6W 3000K ruggine

| | | | | | | | |
|--|-------------------------|-----------------|-----------------------------|----------------|-------------------------|------------|--------------------|
| Luminaire Flux | 765 lm | Luminaire Power | 13.0 W | Efficacy | 58.880 lm/W | Efficiency | 100.00% |
| Source Flux | 765 lm | Maximum value | 251.23 cd/klm | Position | C=90.00 G=60.00 | CG | Double Symmetrical |
| Rectangular Luminaire Round Luminous Area | Length Diam. | 50 mm 90 mm | Width Height | 170 mm 0 mm | Height | 1 mm | |
| Horizontal Luminous Area | 0.006362 m ² | | Emitting area on Plane 180° | | 0.000000 m ² | | |
| Emitting area on Plane 0° | 0.000000 m ² | | Emitting area on Plane 270° | | 0.000000 m ² | | |
| Emitting area on Plane 90° | 0.000000 m ² | | Glare area at 76° | | 0.001539 m ² | | |
| Coordinate system | CG | | Symmetry Type | | Double Symmetrical | | |
| Date | 17-05-2013 | | Maximum Gamma Angle | | 180 | | |
| Measurement Distance | 0.00 | | Measurement Flux | | 765 lm | | |


LED Flux=1190,6lm LED Power=10W Eff=64% EfcLed=119lm/W EfcLum=59lm/W CCT=3000K Ra=90 SDCM=2 L90(20K)=118000h

C.I.E. 23 52 79 79 100
F UTE 0.79 J + 0.21 T

D DIN 5040
B NBN

B11
BZ 9 / 0.8 / BZ 8 / 2.5 / BZ 7

50mm x 170mm



Semipiani C

180.0 ——— 0.0
270.0 ——— 90.0

ULOR 21.03 %
DLOR 78.97 %
RN 21.03 %

