

Luminaire

Code T4302ELW00
Name Spike 18 LED 3000K Ellittico

Measurement

Code FTS1500857
Name Spike 18 LED 3000K Ellittico


Luminaire Flux	3163 lm	Luminaire Power	36.0 W	Efficacy	87.869 lm/W	Efficiency	100.00%
Source Flux	3163 lm	Maximum value	3215.71 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	726 mm	Width	35 mm	Height	35 mm
Rectangular Luminous Area		Length	722 mm	Width	30 mm	Height	0 mm
Horizontal Luminous Area		0.021660 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.005240 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		17-01-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3163 lm	

LED Flux=3564lm LED Power=36W Eff=89% EfcLed=99lm/W EfcLum=88lm/W CCT=3000K Ra=80 R9=7 SDCM=3 L70(6K)=272160h

C.I.E. 90 97 99 100 100
F UTE 1.00 A

D DIN 5040
B NBN
A60
BZ 1

726mm x 35mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 0.00 %
DLOR 100.00 %
RN 0.00 %

