

Luminaire

Code TC41104
Name GOPLE 80 PENDANT TRK12 930 SP BLACK

Measurerm.

Code FTS2200232
Name GOPLE 80 PENDANT TRK12 930 SP BLACK

Luminaire Flux	1767 lm	Luminaire Power	24.0 W	Efficacy	73.626 lm/W	Efficiency	100.00%
Source Flux	1767 lm	Maximum value	8894.53 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	77 mm	Height	150 mm		
Round Luminous Area		Diam.	46 mm	Height	0 mm		
Horizontal Luminous Area		0.001662 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000402 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-09-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1767 lm	

LED Flux=2435lm LED Power=22W Eff=73% EfcLed=113lm/W EfcLum=74lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(6K)=50000h

C.I.E. 99 100 100 100 100
F UTE --

D DIN 5040
B NBN

A60
BZ 1


Diam=77mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
DLOR 100.00 %
RN 0.00 %



Luminaire

Code TC41104
Name GOPLE 80 PENDANT TRK12 930 SP BLACK

Measurerm.


Code FTS2200232
Name GOPLE 80 PENDANT TRK12 930 SP BLACK

Luminaire Flux	1767 lm	Luminaire Power	24.0 W	Efficacy	73.626 lm/W	Efficiency	100.00%
Source Flux	1767 lm	Maximum value	8894.53 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	77 mm	Height	150 mm		
Round Luminous Area		Diam.	46 mm	Height	0 mm		
Horizontal Luminous Area		0.001662 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000402 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-09-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1767 lm	
LED Flux=2435lm LED Power=22W Eff=73% EfcLed=113lm/W EfcLum=74lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(6K)=50000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.14	0.27	0.41	0.54	0.68	OC	0.14	0.27	0.41	0.54	0.68
OB	0.14	0.27	0.41	0.54	0.68	OD	0.14	0.27	0.41	0.54	0.68

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	15716.90	12273.99	1954.67	563.64	15.84	6.85	4.00	2.83	1.47	0.51
OB	15716.90	12273.99	1954.67	563.64	15.84	6.85	4.00	2.83	1.47	0.51
OC	15716.90	12273.99	1954.67	563.64	15.84	6.85	4.00	2.83	1.47	0.51
OD	15716.90	12273.99	1954.67	563.64	15.84	6.85	4.00	2.83	1.47	0.51



H[m]	D[m]	Max lux	Med lux	Alpha=7.7°+7.7°	G=0.0
1.00	0.27	15717	10288		
2.00	0.54	3929	2572		
3.00	0.81	1746	1143		
4.00	1.09	982	643		
5.00	1.36	629	412		