

Luminaire

Code TC43104+AP91400
 Name GOPLE 80 PENDANT TRK12 940 SP BLACK + ANTI-DUZZLE LOUVRE

Measurem.

Code FTS2200242
 Name GOPLE 80 PENDANT TRK12 940 SP BLACK + ANTI-DUZZLE LOUVRE

| | | | | | | | |
|--|---------|-----------------|----------------|-----------------------------|---------------|-----------------|-----------------|
| Luminaire Flux | 1039 lm | Luminaire Power | 24.0 W | Efficacy | 43.287 lm/W | Efficiency | 100.00% |
| Source Flux | 1039 lm | Maximum value | 9643.54 cd/klm | Position | C=0.00 G=0.00 | CG | Rotosymmetrical |
| Round Luminaire | | Diam. | 77 mm | Height | 150 mm | | |
| Round Luminous Area | | Diam. | 46 mm | Height | 0 mm | | |
| Horizontal Luminous Area | | 0.001662 m2 | | Emitting area on Plane 180° | | 0.000000 m2 | |
| Emitting area on Plane 0° | | 0.000000 m2 | | Emitting area on Plane 270° | | 0.000000 m2 | |
| Emitting area on Plane 90° | | 0.000000 m2 | | Glare area at 76° | | 0.000402 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Rotosymmetrical | |
| Date | | 21-09-2022 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 1039 lm | |
| LED Flux=2473lm LED Power=22W Eff=42% EfcLed=114lm/W EfcLum=43lm/W CCT=4000K Ra=90 R9=50 SDCM=3 L70(6K)=50000h | | | | | | | |
| C.I.E. | 100 | 100 | 100 | 100 | D DIN 5040 | A60 | |
| F UTE | -- | | | | B NBN | BZ 1 | |

Diam=77mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



