

## Luminaire

Code TC53204+AP90300  
 Name GOPLE 60 PENDANT TRK12 940 FL BLACK + SOFT FILTER

## Measurement

Code FTS2200209  
 Name GOPLE 60 PENDANT TRK12 940 FL BLACK + SOFT FILTER

Luminaire Flux	440 lm	Luminaire Power	10.0 W	Efficacy	43.970 lm/W	Efficiency	100.00%
Source Flux	440 lm	Maximum value	3823.34 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	55 mm	Height	110 mm		
Round Luminous Area		Diam.	35 mm	Height	0 mm		
Horizontal Luminous Area			0.000962 m2	Emitting area on Plane 180°			0.000000 m2
Emitting area on Plane 0°			0.000000 m2	Emitting area on Plane 270°			0.000000 m2
Emitting area on Plane 90°			0.000000 m2	Glare area at 76°			0.000233 m2
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-09-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		440 lm	
LED Flux=929lm LED Power=7.9W Eff=47% EfcLed=117lm/W EfcLum=44lm/W CCT=4000K Ra=90 R9=50 SDCM=2 L70(6K)=50000h							
C.I.E.	97 99 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		


Diam=55mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %  
 DLOR 100.00 %  
 RN 0.00 %



## Luminaire

Code TC53204+AP90300  
Name GOPLE 60 PENDANT TRK12 940 FL BLACK + SOFT FILTER

## Measurem.


Code FTS2200209  
Name GOPLE 60 PENDANT TRK12 940 FL BLACK + SOFT FILTER

Luminaire Flux	440 lm	Luminaire Power	10.0 W	Efficacy	43.970 lm/W	Efficiency	100.00%
Source Flux	440 lm	Maximum value	3823.34 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	55 mm	Height	110 mm		
Round Luminous Area		Diam.	35 mm	Height	0 mm		
Horizontal Luminous Area		0.000962 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000233 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-09-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		440 lm	
LED Flux=929lm LED Power=7.9W Eff=47% EfcLed=117lm/W EfcLum=44lm/W CCT=4000K Ra=90 R9=50 SDCM=2 L70(6K)=50000h							
C.I.E.	97 99 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.23	0.45	0.68	0.91	1.14	OC	0.23	0.45	0.68	0.91	1.14
OB	0.23	0.45	0.68	0.91	1.14	OD	0.23	0.45	0.68	0.91	1.14

	Luminous Intensities [ cd/klm ]									
	0	5	15	25	35	45	55	65	75	85
OA	1681.12	1505.28	663.10	180.20	39.77	9.37	3.10	1.71	0.86	0.23
OB	1681.12	1505.28	663.10	180.20	39.77	9.37	3.10	1.71	0.86	0.23
OC	1681.12	1505.28	663.10	180.20	39.77	9.37	3.10	1.71	0.86	0.23
OD	1681.12	1505.28	663.10	180.20	39.77	9.37	3.10	1.71	0.86	0.23



H[m]	D[m]	Max lux	Med lux	Alpha=12.8°+12.8°	G=0.0
1.00	0.45	1681	1043		
2.00	0.91	420	261		
3.00	1.36	187	116		
4.00	1.82	105	65		
5.00	2.27	67	42		