

## Luminaire

Code 1713010A  
Name METEORITE 48 SOSPENSIONE

## Measurerm.

Code FTS1503249  
Name METEORITE 48 SOSPENSIONE

Luminaire Flux	1904 lm	Luminaire Power	21.0 W	Efficacy	90.677 lm/W	Efficiency	77.66%
Source Flux	2452 lm	Maximum value	64.86 cd/klm	Position	C=0.00 G=103.00	CG	Rotosymmetrical
Round Luminaire		Diam.	480 mm	Height	480 mm		
Round Luminous Area		Diam.	480 mm	Height	480 mm		
Horizontal Luminous Area		0.180956 m <sup>2</sup>		Emitting area on Plane 180°		0.230400 m <sup>2</sup>	
Emitting area on Plane 0°		0.230400 m <sup>2</sup>		Emitting area on Plane 270°		0.230400 m <sup>2</sup>	
Emitting area on Plane 90°		0.230400 m <sup>2</sup>		Glare area at 76°		0.267333 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		17-12-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2452 lm	
Lamping=LED DIM 1x21W (E27) CCT=2700K CRI=80							
C.I.E.	25 49 75 51 78			D DIN 5040		C11	
F UTE	0.40 J + 0.38 T			B NBN		BZ 8	

Diam=480mm



Semipiani C

180.0 ——— 0.0

ULOR 37.90 %

DLOR 39.76 %

RN 48.80 %

