

## Luminaire

Code 0564030A+0780020A  
 Name TOLOMEO MEGA BODY BLK C/INTER. + TOLOMEO MEGA DIFF.PERG.360

## Measurement


Code FTS001995-A  
 Name TOLOMEO MEGA BODY BLK C/INTER. + TOLOMEO MEGA DIFF.PERG.360

Luminaire Flux	2067 lm	Luminaire Power	21.0 W	Efficacy	98.449 lm/W	Efficiency	84.32%
Source Flux	2452 lm	Maximum value	161.33 cd/klm	Position	C=45.00 G=35.00	CG	Double Symmetrical
Round Luminaire		Diam.	360 mm	Height	255 mm		
Round Luminous Area		Diam.	360 mm	Height	255 mm		
Horizontal Luminous Area		0.101788 m <sup>2</sup>		Emitting area on Plane 180°		0.091800 m <sup>2</sup>	
Emitting area on Plane 0°		0.091800 m <sup>2</sup>		Emitting area on Plane 270°		0.091800 m <sup>2</sup>	
Emitting area on Plane 90°		0.091800 m <sup>2</sup>		Glare area at 76°		0.113698 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		22-12-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2452 lm	


Lamping=LED DIM 1x21W (E27) CCT=2700K CRI=80

C.I.E. 46 78 92 63 84  
 F UTE 0.53 E + 0.32 T

D DIN 5040 B31  
 B NBN BZ 5



ULOR 31.61 %  
 DLOR 52.71 %  
 RN 37.49 %



## Luminaire

Code 0564030A+0780020A  
 Name TOLOMEO MEGA BODY BLK C/INTER. + TOLOMEO MEGA DIFF.PERG.360

## Measurerm.


Code FTS001995-A  
 Name TOLOMEO MEGA BODY BLK C/INTER. + TOLOMEO MEGA DIFF.PERG.360

Luminaire Flux	2067 lm	Luminaire Power	21.0 W	Efficacy	98.449 lm/W	Efficiency	84.32%
Source Flux	2452 lm	Maximum value	161.33 cd/klm	Position	C=45.00 G=35.00	CG	Double Symmetrical
Round Luminaire		Diam.	360 mm	Height	255 mm		
Round Luminous Area		Diam.	360 mm	Height	255 mm		
Horizontal Luminous Area		0.101788 m2		Emitting area on Plane 180°		0.091800 m2	
Emitting area on Plane 0°		0.091800 m2		Emitting area on Plane 270°		0.091800 m2	
Emitting area on Plane 90°		0.091800 m2		Glare area at 76°		0.113698 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		22-12-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2452 lm	
Lamping=LED DIM 1x21W (E27) CCT=2700K CRI=80							
C.I.E.	46 78 92 63 84			D DIN 5040	B31		
F UTE	0.53 E + 0.32 T			B NBN	BZ 5		

### Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	1.49	2.99	4.48	5.98	7.47	OC	1.49	2.98	4.47	5.96	7.45
OB	1.49	2.99	4.48	5.98	7.47	OD	1.49	2.98	4.47	5.96	7.45

	Luminous Intensities [ cd/klm ]									
	0	5	15	25	35	45	55	65	75	85
OA	367.58	366.10	361.50	380.32	395.57	344.34	213.86	115.08	83.09	64.27
OB	367.58	366.10	361.50	380.32	395.57	344.34	213.86	115.08	83.09	64.27
OC	367.58	366.40	362.83	380.68	395.25	345.29	212.49	115.24	82.68	63.80
OD	367.58	366.40	362.83	380.68	395.25	345.29	212.49	115.24	82.68	63.80



H[m]	D[m]	Max lux	Med lux	Alpha=56.2°+56.2°	G=0.0 Max non a G
1.00	2.99	368	110		
2.00	5.98	92	28		
3.00	8.97	41	12		
4.00	11.95	23	7		
5.00	14.94	15	4		

H[m]	D[m]	Max lux	Med lux	Beta=56.1°+56.1°	G=0.0 Max non a G
1.00	2.98	368	110		
2.00	5.96	92	28		
3.00	8.94	41	12		
4.00	11.91	23	7		
5.00	14.89	15	4		