

Luminaire

Code T4303ELW00
Name Spike 24 LED 3000K Ellittico

Measurement

Code FTS1500863
Name Spike 24 LED 3000K Ellittico

Luminaire Flux	4218 lm	Luminaire Power	48.0 W	Efficacy	87.869 lm/W	Efficiency	100.00%
Source Flux	4218 lm	Maximum value	3215.71 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	966 mm	Width	35 mm	Height	35 mm
Rectangular Luminous Area		Length	962 mm	Width	30 mm	Height	0 mm
Horizontal Luminous Area		0.028860 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.006982 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		17-01-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4218 lm	
LED Flux=4752lm LED Power=48W Eff=89% EfcLed=99lm/W EfcLum=88lm/W CCT=3000K Ra=80 R9=7 SDCM=3 L70(6K)=272160h							
C.I.E.	90 97 99 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		



