

## Luminaire

Code 0112010A  
Name DIOSCURI PAR/SOFF 250

## Measurerm.

Code FTS0002521  
Name DIOSCURI PAR/SOFF 250

Luminaire Flux	1356 lm	Luminaire Power	13.0 W	Efficacy	104.284 lm/W	Efficiency	89.13%
Source Flux	1521 lm	Maximum value	76.32 cd/klm	Position	C=0.00 G=15.00	CG	Rotosymmetrical
Round Luminaire		Diam.	250 mm	Height	250 mm		
Round Luminous Area		Diam.	250 mm	Height	250 mm		
Horizontal Luminous Area		0.049087 m <sup>2</sup>		Emitting area on Plane 180°		0.062500 m <sup>2</sup>	
Emitting area on Plane 0°		0.062500 m <sup>2</sup>		Emitting area on Plane 270°		0.062500 m <sup>2</sup>	
Emitting area on Plane 90°		0.062500 m <sup>2</sup>		Glare area at 76°		0.072519 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		16-12-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1521 lm	
Lamping=LED DIM 1x13W (E27) CCT=2700K CRI=80							
C.I.E.	25 50 75 53 89			D DIN 5040		C11	
F UTE	0.48 J + 0.42 T			B NBN		BZ 8	

Diam=250mm



Semipiani C

180.0 ——— 0.0

ULOR 41.57 %

DLOR 47.56 %

RN 46.64 %

