

Luminaire


Code 0846030A
Name LOGICO MICRO PARETE HALO

Measurment

Code FTS161366-A
Name LOGICO MICRO PARETE HALO

Luminaire Flux	279 lm	Luminaire Power	5.0 W	Efficacy	55.700 lm/W	Efficiency	59.26%
Source Flux	470 lm	Maximum value	168.98 cd/klm	Position	C=75.00 G=50.00	CG	Asymmetrical
Rectangular Luminaire		Length	220 mm	Width	103 mm	Height	253 mm
Rectangular Luminous Area		Length	220 mm	Width	103 mm	Height	252 mm
Horizontal Luminous Area		0.022660 m2		Emitting area on Plane 180°		0.055660 m2	
Emitting area on Plane 0°		0.055660 m2		Emitting area on Plane 270°		0.026059 m2	
Emitting area on Plane 90°		0.026059 m2		Glare area at 76°		0.059489 m2	
Coordinate system		CG		Symmetry Type		Asymmetrical	
Date		20-01-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		470 lm	
Lamping=LED DIM 1x5W (E14) CCT=2700K CRI=80							
C.I.E.	33 62 83 66 59			D DIN 5040	B21		
F UTE	0.39 H + 0.20 T			B NBN	BZ 6		

220mm x 103mm



Sempiani C

180.0 ——— 0.0
270.0 ——— 90.0

ULOR 20.21 %
DLOR 39.04 %
RN 34.11 %

