

## Luminaire

Code DAL0027014  
Name STABLIGHT C S AQUAMARINE

## Measurement

Code FTS1603801  
Name STABLIGHT C S AQUAMARINE

Luminaire Flux	340 lm	Luminaire Power	5.5 W	Efficacy	61.727 lm/W	Efficiency	97.00%
Source Flux	350 lm	Maximum value	2241.60 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	212 mm	Height	172 mm		
Round Luminous Area		Diam.	50 mm	Height	0 mm		
Horizontal Luminous Area			0.001963 m <sup>2</sup>	Emitting area on Plane 180°			0.000000 m <sup>2</sup>
Emitting area on Plane 0°			0.000000 m <sup>2</sup>	Emitting area on Plane 270°			0.000000 m <sup>2</sup>
Emitting area on Plane 90°			0.000000 m <sup>2</sup>	Glare area at 76°			0.000475 m <sup>2</sup>
Coordinate system		CG		Symmetry Type			Rotosymmetrical
Date		20-12-2021		Maximum Gamma Angle			180
Measurement Distance		0.00		Measurement Flux			350 lm

Lamping=LED DIM 1x6W 36° PAR (GU10) CCT=3000K CRI=90

C.I.E. 89 98 100 100 97  
F UTE 0.97 A

D DIN 5040  
B NBN  
A60  
BZ 1

Diam=212mm




Semipiani C

180.0 ——— 0.0

ULOR 0.01 %

DLOR 96.99 %

RN 0.01 %



## Luminaire

Code DAL0027014  
Name STABLIGHT C S AQUAMARINE

## Measurerm.

Code FTS1603801  
Name STABLIGHT C S AQUAMARINE


Luminaire Flux	340 lm	Luminaire Power	5.5 W	Efficacy	61.727 lm/W	Efficiency	97.00%
Source Flux	350 lm	Maximum value	2241.60 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	212 mm	Height	172 mm		
Round Luminous Area		Diam.	50 mm	Height	0 mm		
Horizontal Luminous Area		0.001963 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000475 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		20-12-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		350 lm	
Lamping=LED DIM 1x6W 36° PAR (GU10) CCT=3000K CRI=90							
C.I.E.	89 98 100 100 97			D DIN 5040	A60		
F UTE	0.97 A			B NBN	BZ 1		

### Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.28	0.57	0.85	1.14	1.42	OC	0.28	0.57	0.85	1.14	1.42
OB	0.28	0.57	0.85	1.14	1.42	OD	0.28	0.57	0.85	1.14	1.42

### Luminous Intensities [ cd/klm]

	0	5	15	25	35	45	55	65	75	85
OA	784.56	729.56	421.64	169.88	61.30	25.13	12.76	6.32	1.32	0.48
OB	784.56	729.56	421.64	169.88	61.30	25.13	12.76	6.32	1.32	0.48
OC	784.56	729.56	421.64	169.88	61.30	25.13	12.76	6.32	1.32	0.48
OD	784.56	729.56	421.64	169.88	61.30	25.13	12.76	6.32	1.32	0.48



H[m]	D[m]	Max lux	Med lux	Alpha=15.9°+15.9°	G=0.0
1.00	0.57	785	475		
2.00	1.14	196	119		
3.00	1.71	87	53		
4.00	2.28	49	30		
5.00	2.85	31	19		