


Luminaire

Code AD02204
Name Picto 70 New led Verticale DIM Nero 3000K wide flood

Measurem.

Code FTS1602987
Name Picto 70 New led Verticale DIM Nero 3000K wide flood

Luminaire Flux	1779.82 lm	Luminaire Power	20.00 W	Efficacy	88.99 lm/W	Efficiency	100.00%
Lamps Flux	1779.82 lm	Maximum value	1580.38 cd/klm	Position	C=0.00 G=2.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area	Diam. 70 mm Diam. 35 mm	Height	100 mm	Height	0 mm		
Horizontal Luminous Area	0.000962 m2	Emitting area on Plane 180°			0.000000 m2		
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°			0.000000 m2		
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°			0.000233 m2		
Coordinate system	CG	Symmetry Type			Rotosymmetrical		
Date	29-08-2017	Maximum Gamma Angle			180		
Measurement Distance	0.00	Measurement Flux			1779.82 lm		
LED Flux=2046lm LED Power=17,5W Eff=86,99% EfcLed=117lm/W EfcLum=89lm/W Ra=90 SDCM=3 L70(6K)=60000h							
C.I.E.	97 99 100 100 100	D DIN 5040			A60		
F UTE	1.00 A	B NBN			BZ 1		



Luminaire

Code AD02204
Name Picto 70 New led Verticale DIM Nero 3000K wide flood

Measur.


Code FTS1602987
Name Picto 70 New led Verticale DIM Nero 3000K wide flood

Luminaire Flux	1779.82 lm	Luminaire Power	20.00 W	Efficacy	88.99 lm/W	Efficiency	100.00%
Lamps Flux	1779.82 lm	Maximum value	1580.38 cd/klm	Position	C=0.00 G=2.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area		Diam. Diam.	70 mm 35 mm	Height Height	100 mm 0 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.000962 m2 0.000000 m2 0.000000 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.000000 m2 0.000000 m2 0.000233 m2	
Coordinate system Date Measurement Distance		CG 29-08-2017 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 180 1779.82 lm	
LED Flux=2046lm LED Power=17,5W Eff=86,99% EfcLed=117lm/W EfcLum=89lm/W Ra=90 SDCM=3 L70(6K)=60000h							
C.I.E. F UTE	97 99 100 100 100 1.00 A			D DIN 5040 B NBN	A60 BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.39	0.78	1.17	1.57	1.96	OC	0.39	0.78	1.17	1.57	1.96
OB	0.39	0.78	1.17	1.57	1.96	OD	0.39	0.78	1.17	1.57	1.96

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	2807.68	2803.81	2178.74	1110.53	521.70	53.64	10.21	5.19	3.20	1.36
OB	2807.68	2803.81	2178.74	1110.53	521.70	53.64	10.21	5.19	3.20	1.36
OC	2807.68	2803.81	2178.74	1110.53	521.70	53.64	10.21	5.19	3.20	1.36
OD	2807.68	2803.81	2178.74	1110.53	521.70	53.64	10.21	5.19	3.20	1.36



H[m]	D[m]	Max lux	Med lux	Alpha=21.4°+21.4°	G=0.0 Max non a G
1.00	0.78	2809	1708		
2.00	1.57	702	427		
3.00	2.35	312	190		
4.00	3.13	176	107		
5.00	3.91	112	68		