

## Luminaire


Code AF36004+AF95104  
 Name SHARP SMD.2X 5,5W 927 FL EXD NRO+ SCREEN 2X BLACK

## Measurement

Code FTS1901848  
 Name SHARP SMD.2X 5,5W 927 FL EXD NRO+ SCREEN 2X BLACK

Luminaire Flux	395 lm	Luminaire Power	6.5 W	Efficacy	60.794 lm/W	Efficiency	100.00%
Source Flux	395 lm	Maximum value	5604.42 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	78 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	72 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.002664 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000644 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		09-11-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		395 lm	
LED Flux=530lm LED Power=5.5W Eff=75% EfcLed=96lm/W EfcLum=61lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(6K)=272160h							
C.I.E.	100	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1


78mm x 45mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %  
 DLOR 100.00 %  
 RN 0.00 %



## Luminaire

Code AF36004+AF95104  
Name SHARP SMD.2X 5,5W 927 FL EXD NRO+ SCREEN 2X BLACK

## Measurem.


Code FTS1901848  
Name SHARP SMD.2X 5,5W 927 FL EXD NRO+ SCREEN 2X BLACK

Luminaire Flux	395 lm	Luminaire Power	6.5 W	Efficacy	60.794 lm/W	Efficiency	100.00%
Source Flux	395 lm	Maximum value	5604.42 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	78 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	72 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.002664 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000644 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		09-11-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		395 lm	
LED Flux=530lm LED Power=5.5W Eff=75% EfcLed=96lm/W EfcLum=61lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(6K)=272160h							
C.I.E.	100	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.18	0.35	0.53	0.70	0.88	OC	0.18	0.35	0.53	0.70	0.88
OB	0.18	0.35	0.53	0.70	0.88	OD	0.18	0.35	0.53	0.70	0.88

	Luminous Intensities [ cd/klm ]									
	0	5	15	25	35	45	55	65	75	85
OA	2214.64	1883.19	578.20	154.67	9.16	1.94	0.24	0.00	0.00	0.00
OB	2214.64	1883.19	578.20	154.67	9.16	1.94	0.24	0.00	0.00	0.00
OC	2214.64	1883.19	578.20	154.67	9.16	1.94	0.24	0.00	0.00	0.00
OD	2214.64	1883.19	578.20	154.67	9.16	1.94	0.24	0.00	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=10.0°+10.0°	G=0.0
1.00	0.35	2215	1413		
2.00	0.70	554	353		
3.00	1.05	246	157		
4.00	1.40	138	88		
5.00	1.75	89	57		