

## Luminaire

Code AF65300+AF95201  
 Name SHARP RECESSED TRIMLESS 8X 24W 940 FLOOD EXT.DRV + SCREEN 4X WHITE

## Measurem.

Code FTS1603383  
 Name SHARP RECESSED TRIMLESS 8X 24W 940 FLOOD EXT.DRV + SCREEN 4X WHITE

Luminaire Flux	1720.77 lm	Luminaire Power	22.00 W	Efficacy	78.22 lm/W	Efficiency	100.00%
Lamps Flux	1720.77 lm	Maximum value	5541.55 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	298 mm	Width	40 mm	Height	55 mm
Rectangular Luminous Area		Length	296 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.010952 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.002650 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1720.77 lm	


LED Flux=2271,96lm LED Power=22W Eff=76% EfcLed=103lm/W EfcLum=78lm/W Ra=90 SDCM=2 L90(20K)=118000h

C.I.E. 99 100 100 100 100  
 F UTE --

D DIN 5040  
 B NBN

A60  
 BZ 1


298mm x 40mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %  
 DLOR 100.00 %  
 RN 0.00 %



## Luminaire

Code AF65300+AF95201  
Name SHARP RECESSED TRIMLESS 8X 24W 940 FLOOD EXT.DRV + SCREEN 4X WHITE

## Measurerm.


Code FTS1603383  
Name SHARP RECESSED TRIMLESS 8X 24W 940 FLOOD EXT.DRV + SCREEN 4X WHITE

Luminaire Flux	1720.77 lm	Luminaire Power	22.00 W	Efficacy	78.22 lm/W	Efficiency	100.00%
Lamps Flux	1720.77 lm	Maximum value	5541.55 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	298 mm	Width	40 mm	Height	55 mm
Rectangular Luminous Area		Length	296 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.010952 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.002650 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1720.77 lm	
LED Flux=2271,96lm LED Power=22W Eff=76% EfcLed=103lm/W EfcLum=78lm/W Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

### Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.18	0.35	0.53	0.70	0.88	OC	0.18	0.35	0.53	0.70	0.88
OB	0.18	0.35	0.53	0.70	0.88	OD	0.18	0.35	0.53	0.70	0.88

	Luminous Intensities [ cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	9535.74	8114.95	2503.56	684.52	42.95	12.12	4.21	2.70	1.91	0.90
OB	9535.74	8114.95	2503.56	684.52	42.95	12.12	4.21	2.70	1.91	0.90
OC	9535.74	8114.95	2503.56	684.52	42.95	12.12	4.21	2.70	1.91	0.90
OD	9535.74	8114.95	2503.56	684.52	42.95	12.12	4.21	2.70	1.91	0.90



H[m]	D[m]	Max lux	Med lux	Alpha=10.0°+10.0°	G=0.0
1.00	0.35	9536	6080		
2.00	0.70	2384	1520		
3.00	1.05	1060	676		
4.00	1.41	596	380		
5.00	1.76	381	243		