

## Luminaire

Code AE25000+AE42001  
 Name A. SHARPING 2368.DIR+IND 4X4 930 DM FLOOD + SCREENS 2368 4X4 WHITE

## Measurem.

Code FTS1603110  
 Name A. SHARPING 2368.DIR+IND 4X4 930 DM FLOOD + SCREENS 2368 4X4 WHITE

|   |                   |                 |                |                             |               |                    |                    |
|---|-------------------|-----------------|----------------|-----------------------------|---------------|--------------------|--------------------|
| Luminaire Flux  | 8247.97 lm        | Luminaire Power | 104.00 W       | Efficacy                    | 79.31 lm/W    | Efficiency         | 100.00%            |
| Lamps Flux  | 8247.97 lm        | Maximum value   | 2215.04 cd/klm | Position                    | C=0.00 G=0.00 | CG                 | Double Symmetrical |
| Rectangular Luminaire   |                   | Length          | 2368 mm        | Width                       | 40 mm         | Height             | 111 mm             |
| Rectangular Luminous Area   |                   | Length          | 592 mm         | Width                       | 37 mm         | Height             | 0 mm               |
| Horizontal Luminous Area  |                   | 0.021904 m2     |                | Emitting area on Plane 180° |               | 0.000000 m2        |                    |
| Emitting area on Plane 0°   |                   | 0.000000 m2     |                | Emitting area on Plane 270° |               | 0.000000 m2        |                    |
| Emitting area on Plane 90°  |                   | 0.000000 m2     |                | Glare area at 76°           |               | 0.005299 m2        |                    |
| Coordinate system   |                   | CG              |                | Symmetry Type               |               | Double Symmetrical |                    |
| Date  |                   | 21-02-2017      |                | Maximum Gamma Angle         |               | 180                |                    |
| Measurement Distance  |                   | 0.00            |                | Measurement Flux            |               | 8247.97 lm         |                    |
| LED Flux=10782,4lm LED Power=95W Eff=76% EfcLed=113lm/W EfcLum=79lm/W Ra=90 SDCM=2 L90(20K)=118000h |                   |                 |                |                             |               |                    |                    |
| C.I.E.  | 99 100 100 40 100 |                 |                | D DIN 5040                  |               | D62                |                    |
| F UTE   | --                |                 |                | B NBN                       |               | BZ 1               |                    |



