

Luminaire

Code M329765_0°
Name EVERY 105 CA TR OR LED 2700K 2X14°ME/S_0°

Measurement

Code FTS2400266.
Name EVERY 105 CA TR OR LED 2700K 2X14°ME/S_0°

Luminaire Flux	872 lm	Luminaire Power	10.0 W	Efficacy	87.200 lm/W	Efficiency	100.00%
Source Flux	872 lm	Maximum value	1063.07 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	85 mm	Width	85 mm	Height	130 mm
Rectangular Luminous Area		Length	80 mm	Width	80 mm	Height	0 mm
Horizontal Luminous Area		0.006400 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.001548 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		06-06-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		872 lm	
LED Flux=1474lm LED Power=10W Eff=59% EfcLed=147lm/W EfcLum=87lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(9k)=50000h							
C.I.E.	93 100 100 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		


85mm x 85mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
DLOR 100.00 %
RN 0.00 %



Luminaire

Code M329765_0°
Name EVERY 105 CA TR OR LED 2700K 2X14°ME/S_0°

Measurment.


Code FTS2400266.
Name EVERY 105 CA TR OR LED 2700K 2X14°ME/S_0°

Luminaire Flux	872 lm	Luminaire Power	10.0 W	Efficacy	87.200 lm/W	Efficiency	100.00%
Source Flux	872 lm	Maximum value	1063.07 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire Rectangular Luminous Area	Length Length	85 mm 80 mm	Width Width	85 mm 80 mm	Height Height	130 mm 0 mm	
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°	0.006400 m2 0.000000 m2 0.000000 m2	Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°	0.000000 m2 0.000000 m2 0.001548 m2				
Coordinate system Date Measurement Distance	CG 06-06-2024 0.00	Symmetry Type Maximum Gamma Angle Measurement Flux	Rotosymmetrical 180 872 lm				
LED Flux=1474lm LED Power=10W Eff=59% EfcLed=147lm/W EfcLum=87lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(9k)=50000h							
C.I.E. F UTE	93 100 100 100 100 1.00 A	D DIN 5040 B NBN	A60 BZ 1				

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.58	1.15	1.73	2.31	2.89	OC	0.58	1.15	1.73	2.31	2.89
OB	0.58	1.15	1.73	2.31	2.89	OD	0.58	1.15	1.73	2.31	2.89

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	926.99	916.52	823.12	614.70	316.19	83.27	9.46	0.39	0.29	0.25
OB	926.99	916.52	823.12	614.70	316.19	83.27	9.46	0.39	0.29	0.25
OC	926.99	916.52	823.12	614.70	316.19	83.27	9.46	0.39	0.29	0.25
OD	926.99	916.52	823.12	614.70	316.19	83.27	9.46	0.39	0.29	0.25



H[m]	D[m]	Max lux	Med lux	Alpha=30.0°+30.0°	G=0.0
1.00	1.15	927	487		
2.00	2.31	232	122		
3.00	3.46	103	54		
4.00	4.62	58	30		
5.00	5.77	37	19		