

Luminaire

Code M323905
Name EVERYTHING 150 TONDO TRIMLESS ORIENTABILE LED FLOOD DEFL. NERO 2700K

Measurem.

Code FTS1602593
Name EVERYTHING 150 TONDO TRIMLESS ORIENTABILE LED FLOOD DEFL. NERO 2700K

Luminaire Flux	1957.30 lm	Luminaire Power	24.00 W	Efficacy	81.55 lm/W	Efficiency	100.00%
Sources Flux	1957.30 lm	Maximum value	4914.34 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	150 mm	Height	137 mm		
Round Luminous Area		Diam.	120 mm	Height	0 mm		
Horizontal Luminous Area		0.011310 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.002736 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		04-03-2015		Maximum Gamma Angle		90	
Measurement Distance		0.00		Measurement Flux		1957.30 lm	


LED Flux=2645lm LED Power=24W Eff=74% EfcLed=110lm/W EfcLum=82lm/W Ra=90 SDCM=3 L70(6K)=50000h

C.I.E. 99 100 100 100 100
F UTE --

D DIN 5040
B NBN

A60
BZ 1

Diam=150mm




Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code M323905
Name EVERYTHING 150 TONDO TRIMLESS ORIENTABILE LED FLOOD DEFL. NERO 2700K

Measur.

Code FTS1602593
Name EVERYTHING 150 TONDO TRIMLESS ORIENTABILE LED FLOOD DEFL. NERO 2700K

Luminaire Flux	1957.30 lm	Luminaire Power	24.00 W	Efficacy	81.55 lm/W	Efficiency	100.00%
Sources Flux	1957.30 lm	Maximum value	4914.34 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	150 mm	Height	137 mm		
Round Luminous Area		Diam.	120 mm	Height	0 mm		
Horizontal Luminous Area		0.011310 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.002736 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		04-03-2015		Maximum Gamma Angle		90	
Measurement Distance		0.00		Measurement Flux		1957.30 lm	


LED Flux=2645lm LED Power=24W Eff=74% EfcLed=110lm/W EfcLum=82lm/W Ra=90 SDCM=3 L70(6K)=50000h

C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.16	0.32	0.49	0.65	0.81	OC	0.16	0.32	0.49	0.65	0.81
OB	0.16	0.32	0.49	0.65	0.81	OD	0.16	0.32	0.49	0.65	0.81

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	9618.85	7437.89	2212.62	925.42	378.43	27.28	5.41	0.71	0.23	0.08
OB	9618.85	7437.89	2212.62	925.42	378.43	27.28	5.41	0.71	0.23	0.08
OC	9618.85	7437.89	2212.62	925.42	378.43	27.28	5.41	0.71	0.23	0.08
OD	9618.85	7437.89	2212.62	925.42	378.43	27.28	5.41	0.71	0.23	0.08



H[m]	D[m]	Max lux	Med lux	Alpha=9.2°+9.2°	G=0.0
1.00	0.32	9619	5928		
2.00	0.65	2405	1482		
3.00	0.97	1069	659		
4.00	1.30	601	371		
5.00	1.62	385	237		