


Luminaire

Code 0761W10A+0780030A
 Name TOLOMEO MEGA LED BODY/DIMM + TOLOMEO MEGA DIFF.PERG.420- 2700K

Measurem.

Code FTS1701380
 Name TOLOMEO MEGA LED BODY/DIMM + TOLOMEO MEGA DIFF.PERG.420- 2700K

Luminaire Flux	1884.25 lm	Luminaire Power	31.00 W	Efficacy	60.78 lm/W	Efficiency	100.00%
Lamps Flux	1884.25 lm	Maximum value	438.62 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area		Diam. Diam.	420 mm 420 mm	Height Height	290 mm 290 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.138544 m2 0.121800 m2 0.121800 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.121800 m2 0.121800 m2 0.151699 m2	
Coordinate system Date Measurement Distance		CG 23-09-2016 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 180 1884.25 lm	
LED Flux=2722,9lm LED Power=25,6W Eff=69% EfcLed=106lm/W EfcLum=61lm/W Ra=90 SDCM=2 L70(6K)=50000h							
C.I.E. F UTE	69 85 94 81 100 0.81 C + 0.19 T			D DIN 5040 B NBN		B51 BZ 2 / 0.8 / BZ 3 / 4 / BZ 4	



Luminaire

Code 0761W10A+0780030A
 Name TOLOMEO MEGA LED BODY/DIMM + TOLOMEO MEGA DIFF.PERG.420- 2700K

Measurerm.

Code FTS1701380
 Name TOLOMEO MEGA LED BODY/DIMM + TOLOMEO MEGA DIFF.PERG.420- 2700K

Luminaire Flux	1884.25 lm	Luminaire Power	31.00 W	Efficacy	60.78 lm/W	Efficiency	100.00%
Lamps Flux	1884.25 lm	Maximum value	438.62 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area		Diam. Diam.	420 mm 420 mm	Height Height	290 mm 290 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.138544 m2 0.121800 m2 0.121800 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.121800 m2 0.121800 m2 0.151699 m2	
Coordinate system Date Measurement Distance		CG 23-09-2016 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 180 1884.25 lm	


LED Flux=2722,9lm LED Power=25,6W Eff=69% EfcLed=106lm/W EfcLum=61lm/W Ra=90 SDCM=2 L70(6K)=50000h

C.I.E.	69 85 94 81 100	D DIN 5040	B51
F UTE	0.81 C + 0.19 T	B NBN	BZ 2 / 0.8 / BZ 3 / 4 / BZ 4

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.88	1.76	2.63	3.51	4.39	OC	0.88	1.76	2.63	3.51	4.39
OB	0.88	1.76	2.63	3.51	4.39	OD	0.88	1.76	2.63	3.51	4.39

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	826.48	819.39	771.04	714.53	637.00	171.03	122.34	95.22	71.59	56.66
OB	826.48	819.39	771.04	714.53	637.00	171.03	122.34	95.22	71.59	56.66
OC	826.48	819.39	771.04	714.53	637.00	171.03	122.34	95.22	71.59	56.66
OD	826.48	819.39	771.04	714.53	637.00	171.03	122.34	95.22	71.59	56.66



H[m]	D[m]	Max lux	Med lux	Alpha=41.3°+41.3°	G=0.0
1.00	1.76	826	357		
2.00	3.51	207	89		
3.00	5.27	92	40		
4.00	7.02	52	22		
5.00	8.78	33	14		