

## Luminaire

Code T082020  
Name CHILONE PALO 16W 3000K grigio antracite

## Measurerm.

Code FTS0000905-A  
Name CHILONE PALO 16W 3000K grigio antracite

Luminaire Flux	628 lm	Luminaire Power	14.0 W	Efficacy	44.850 lm/W	Efficiency	100.00%
Source Flux	628 lm	Maximum value	529.54 cd/klm	Position	C=90.00 G=45.00	CG	Asymmetrical
Rectangular Luminaire		Length	168 mm	Width	210 mm	Height	245 mm
Rectangular Luminous Area		Length	28 mm	Width	147 mm	Height	0 mm
Horizontal Luminous Area		0.004116 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000996 m2	
Coordinate system		CG		Symmetry Type		Asymmetrical	
Date		15-04-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		628 lm	


LED Flux=1307lm LED Power=12W Eff=48% EfcLed=105lm/W EfcLum=45lm/W CCT=3000K Ra=80 SDCM=5 L70(6K)=54400

C.I.E. 30 64 88 92 100  
F UTE 0.92 I + 0.08 T

D DIN 5040  
B NBN

A11  
BZ 7 / 0.8 / BZ 6

168mm x 210mm



Semipiani C

180.0 ——— 0.0  
270.0 ——— 90.0

ULOR 8.36 %  
DLOR 91.64 %  
RN 8.36 %

