

Luminaire

Code AQ31304+AQ16XXX
 Name A.24 PLAF. MODULO DIFF.4000K 2352mm BLACK + A.24 SCHERMO DIFF. OPALINO

Measurement

Code FTS2300186
 Name A.24 PLAF. MODULO DIFF.4000K 2352mm BLACK + A.24 SCHERMO DIFF. OPALINO

Luminaire Flux	5685 lm	Luminaire Power	58.0 W	Efficacy	98.017 lm/W	Efficiency	100.00%
Source Flux	5685 lm	Maximum value	349.78 cd/klm	Position	C=90.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2352 mm	Width	27 mm	Height	55 mm
Rectangular Luminous Area		Length	2352 mm	Width	22 mm	Height	0 mm
Horizontal Luminous Area		0.051744 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.012518 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		20-09-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		5685 lm	
LED Flux=9952lm LED Power=53W Eff=57% EfcLed=187lm/W EfcLum=98lm/W CCT=4000K Ra=90 R9=50 SDCM=3 L70(17k)=102000h							
C.I.E.	47 79 96 100 100			D DIN 5040	A30		
F UTE	1.00 E			B NBN	BZ 5 / 2 / BZ 4		



