

Luminaire

Code AN10620+AP91300
Name VECTOR 55 TRACK 930 SP DALI BR.BRONZE + SOFT FILTER

Measurement

Code FTS1800287-B
Name VECTOR 55 TRACK 930 SP DALI BR.BRONZE + SOFT FILTER

Luminaire Flux	1327 lm	Luminaire Power	20.0 W	Efficacy	66.350 lm/W	Efficiency	100.00%
Source Flux	1327 lm	Maximum value	4480.84 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	55 mm	Height	130 mm		
Round Luminous Area		Diam.	48 mm	Height	0 mm		
Horizontal Luminous Area		0.001810 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.000438 m ²	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		28-02-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1327 lm	
LED Flux=2491lm LED Power=17W Eff=53% EfcLed=143lm/W EfcLum=66lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)=50000h							
C.I.E.	98 99 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		


Diam=55mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
DLOR 100.00 %
RN 0.00 %



Luminaire

Code AN10620+AP91300
Name VECTOR 55 TRACK 930 SP DALI BR.BRONZE + SOFT FILTER

Measurerm.


Code FTS1800287-B
Name VECTOR 55 TRACK 930 SP DALI BR.BRONZE + SOFT FILTER

Luminaire Flux	1327 lm	Luminaire Power	20.0 W	Efficacy	66.350 lm/W	Efficiency	100.00%
Source Flux	1327 lm	Maximum value	4480.84 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	55 mm	Height	130 mm		
Round Luminous Area		Diam.	48 mm	Height	0 mm		
Horizontal Luminous Area		0.001810 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000438 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		28-02-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1327 lm	
LED Flux=2491lm LED Power=17W Eff=53% EfcLed=143lm/W EfcLum=66lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)=50000h							
C.I.E.	98 99 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.20	0.41	0.61	0.82	1.02	OC	0.20	0.41	0.61	0.82	1.02
OB	0.20	0.41	0.61	0.82	1.02	OD	0.20	0.41	0.61	0.82	1.02

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	5946.07	5161.21	1994.35	490.47	92.66	19.86	7.50	5.51	3.54	0.96
OB	5946.07	5161.21	1994.35	490.47	92.66	19.86	7.50	5.51	3.54	0.96
OC	5946.07	5161.21	1994.35	490.47	92.66	19.86	7.50	5.51	3.54	0.96
OD	5946.07	5161.21	1994.35	490.47	92.66	19.86	7.50	5.51	3.54	0.96



H[m]	D[m]	Max lux	Med lux	Alpha=11.6°+11.6°	G=0.0
1.00	0.41	5946	3705		
2.00	0.82	1487	926		
3.00	1.23	661	412		
4.00	1.64	372	232		
5.00	2.04	238	148		