

Luminaire

Code AQ44220
Name A.24 SOSP.MOD.D.SHARP3000K XF 2352 BBRZ

Measurement

Code FTS1802293
Name A.24 SOSP.MOD.D.SHARP3000K XF 2352 BBRZ

Luminaire Flux	3461 lm	Luminaire Power	45.0 W	Efficacy	76.920 lm/W	Efficiency	100.00%
Source Flux	3461 lm	Maximum value	1052.56 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2352 mm	Width	27 mm	Height	55 mm
Rectangular Luminous Area		Length	516 mm	Width	12 mm	Height	0 mm
Horizontal Luminous Area		0.006192 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.001498 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		21-11-2018		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3461 lm	
LED Flux=4000.2lm LED Power=38W Eff=87% EfcLed=105lm/W EfcLum=77lm/W CCT=3000K Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	98	100	100	100	D DIN 5040	A60	
F UTE	--				B NBN	BZ 1	



