

Luminaire


Code AQ73418
Name A.24 SOSP CURVA 90 R750 SHRP XF3000K BCP

Measurement

Code FTS1902480-A
Name A.24 SOSP CURVA 90 R750 SHRP XF3000K BCP

Luminaire Flux	1731 lm	Luminaire Power	22.0 W	Efficacy	78.664 lm/W	Efficiency	100.00%
Source Flux	1731 lm	Maximum value	1052.56 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1177 mm	Width	24 mm	Height	55 mm
Rectangular Luminous Area		Length	258 mm	Width	12 mm	Height	0 mm
Horizontal Luminous Area		0.003096 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.000749 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		01-08-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1731 lm	
LED Flux=2000lm LED Power=20W Eff=87% EfcLed=100lm/W EfcLum=79lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(6K)=118000h							
C.I.E.	98	100	100	100	D DIN 5040	A60	
F UTE	--				B NBN	BZ 1	


1177mm x 24mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 0.00 %
DLOR 100.00 %
RN 0.00 %



Luminaire

Code AQ73418
 Name A.24 SOSP CURVA 90 R750 SHRP XF3000K BCP
Measur.
 Code FTS1902480-A
 Name A.24 SOSP CURVA 90 R750 SHRP XF3000K BCP

Luminaire Flux	1731 lm	Luminaire Power	22.0 W	Efficacy	78.664 lm/W	Efficiency	100.00%
Source Flux	1731 lm	Maximum value	1052.56 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1177 mm	Width	24 mm	Height	55 mm
Rectangular Luminous Area		Length	258 mm	Width	12 mm	Height	0 mm
Horizontal Luminous Area	0.003096 m2			Emitting area on Plane 180°	0.000000 m2		
Emitting area on Plane 0°	0.000000 m2			Emitting area on Plane 270°	0.000000 m2		
Emitting area on Plane 90°	0.000000 m2			Glare area at 76°	0.000749 m2		
Coordinate system	CG			Symmetry Type	Double Symmetrical		
Date	01-08-2023			Maximum Gamma Angle	180		
Measurement Distance	0.00			Measurement Flux	1731 lm		


LED Flux=2000lm LED Power=20W Eff=87% EfcLed=100lm/W EfcLum=79lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(6K)=118000h

C.I.E.	98 100 100 100 100	D DIN 5040	A60
F UTE	--	B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.61	1.22	1.83	2.44	3.05	OC	0.62	1.24	1.87	2.49	3.11
OB	0.61	1.22	1.83	2.44	3.05	OD	0.62	1.24	1.87	2.49	3.11

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1821.56	1771.94	1659.04	1369.08	586.81	22.37	4.71	1.26	0.00	0.00
OB	1821.56	1771.94	1659.04	1369.08	586.81	22.37	4.71	1.26	0.00	0.00
OC	1821.56	1774.10	1674.53	1407.42	610.14	21.72	4.67	1.33	0.00	0.00
OD	1821.56	1774.10	1674.53	1407.42	610.14	21.72	4.67	1.33	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=31.4°+31.4°	G=0.0
1.00	1.22	1822	964		
2.00	2.44	455	241		
3.00	3.66	202	107		
4.00	4.88	114	60		
5.00	6.10	73	39		

H[m]	D[m]	Max lux	Med lux	Beta=31.9°+31.9°	G=0.0
1.00	1.24	1822	964		
2.00	2.49	455	241		
3.00	3.73	202	107		
4.00	4.98	114	60		
5.00	6.22	73	39		