

## Luminaire

Code AQ41115+AQ16XXX  
 Name A.24 SOSP. MODULO DIR. DIFF. 4000K 1176mm BSV + A.24 SCHERMO DIFF. OPALINO

## Measurement

Code FTS1800689-A  
 Name A.24 SOSP. MODULO DIR. DIFF. 4000K 1176mm BSV + A.24 SCHERMO DIFF. OPALINO

Luminaire Flux	3418 lm	Luminaire Power	29.0 W	Efficacy	117.862 lm/W	Efficiency	100.00%
Source Flux	3418 lm	Maximum value	347.31 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1176 mm	Width	27 mm	Height	55 mm
Rectangular Luminous Area		Length	1176 mm	Width	22 mm	Height	0 mm
Horizontal Luminous Area		0.025872 m <sup>2</sup>		Emitting area on Plane 180°		0.000000 m <sup>2</sup>	
Emitting area on Plane 0°		0.000000 m <sup>2</sup>		Emitting area on Plane 270°		0.000000 m <sup>2</sup>	
Emitting area on Plane 90°		0.000000 m <sup>2</sup>		Glare area at 76°		0.006259 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		20-09-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3418 lm	

LED Flux=4976lm LED Power=27W Eff=69% EfcLed=187lm/W EfcLum=118lm/W CCT=4000K Ra=90 R9=50 SDCM=3 L70(17k)=102000h

C.I.E. 47 78 95 100 100  
 F UTE 1.00 E

D DIN 5040  
 B NBN

A30  
 BZ 5



