

Luminaire


Code AF47004+AF95204
 Name SHARP SMD.8X 22W 930 FL DIM NRO+ SCREEN 4X BLACK

Measurem.

Code FTS1800886
 Name SHARP SMD.8X 22W 930 FL DIM NRO+ SCREEN 4X BLACK

| | | | | | | | |
|--|------------|-----------------|----------------|-----------------------------|---------------|-----------------|-----------------|
| Luminaire Flux | 1582.00 lm | Luminaire Power | 24.00 W | Efficacy | 65.92 lm/W | Efficiency | 100.00% |
| Lamps Flux | 1582.00 lm | Maximum value | 5604.42 cd/klm | Position | C=0.00 G=0.00 | CG | Rotosymmetrical |
| Rectangular Luminaire | | Length | 298 mm | Width | 40 mm | Height | 55 mm |
| Rectangular Luminous Area | | Length | 296 mm | Width | 37 mm | Height | 0 mm |
| Horizontal Luminous Area | | 0.010952 m2 | | Emitting area on Plane 180° | | 0.000000 m2 | |
| Emitting area on Plane 0° | | 0.000000 m2 | | Emitting area on Plane 270° | | 0.000000 m2 | |
| Emitting area on Plane 90° | | 0.000000 m2 | | Glare area at 76° | | 0.002650 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Rotosymmetrical | |
| Date | | 21-02-2017 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 1582.00 lm | |
| LED Flux=2122,64lm LED Power=22W Eff=75% EfcLed=96lm/W EfcLum=66lm/W Ra=90 SDCM=2 L90(20K)=118000h | | | | | | | |
| C.I.E. | 100 | 100 | 100 | 100 | D DIN 5040 | A60 | |
| F UTE | -- | | | | B NBN | BZ 1 | |


298mm x 40mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
 DLOR 100.00 %
 RN 0.00 %



Luminaire

Code AF47004+AF95204
Name SHARP SMD.8X 22W 930 FL DIM NRO+ SCREEN 4X BLACK

Measurement


Code FTS1800886
Name SHARP SMD.8X 22W 930 FL DIM NRO+ SCREEN 4X BLACK

| | | | | | | | |
|--|------------|-----------------|----------------|-----------------------------|---------------|-----------------|-----------------|
| Luminaire Flux | 1582.00 lm | Luminaire Power | 24.00 W | Efficacy | 65.92 lm/W | Efficiency | 100.00% |
| Lamps Flux | 1582.00 lm | Maximum value | 5604.42 cd/klm | Position | C=0.00 G=0.00 | CG | Rotosymmetrical |
| Rectangular Luminaire | | Length | 298 mm | Width | 40 mm | Height | 55 mm |
| Rectangular Luminous Area | | Length | 296 mm | Width | 37 mm | Height | 0 mm |
| Horizontal Luminous Area | | 0.010952 m2 | | Emitting area on Plane 180° | | 0.000000 m2 | |
| Emitting area on Plane 0° | | 0.000000 m2 | | Emitting area on Plane 270° | | 0.000000 m2 | |
| Emitting area on Plane 90° | | 0.000000 m2 | | Glare area at 76° | | 0.002650 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Rotosymmetrical | |
| Date | | 21-02-2017 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 1582.00 lm | |
| LED Flux=2122,64lm LED Power=22W Eff=75% EfcLed=96lm/W EfcLum=66lm/W Ra=90 SDCM=2 L90(20K)=118000h | | | | | | | |
| C.I.E. | 100 | 100 | 100 | 100 | 100 | D DIN 5040 | A60 |
| F UTE | -- | | | | | B NBN | BZ 1 |

Width at 50.00 % of Max Intensity

| H[m] | 1.00 | 2.00 | 3.00 | 4.00 | 5.00 | H[m] | 1.00 | 2.00 | 3.00 | 4.00 | 5.00 |
|------|------|------|------|------|------|------|------|------|------|------|------|
| OA | 0.18 | 0.35 | 0.53 | 0.70 | 0.88 | OC | 0.18 | 0.35 | 0.53 | 0.70 | 0.88 |
| OB | 0.18 | 0.35 | 0.53 | 0.70 | 0.88 | OD | 0.18 | 0.35 | 0.53 | 0.70 | 0.88 |

| | Luminous Intensities [cd/klm] | | | | | | | | | |
|----|--------------------------------|---------|---------|--------|-------|------|------|------|------|------|
| | 0 | 5 | 15 | 25 | 35 | 45 | 55 | 65 | 75 | 85 |
| OA | 8866.20 | 7539.25 | 2314.78 | 619.20 | 36.66 | 7.75 | 0.98 | 0.00 | 0.00 | 0.00 |
| OB | 8866.20 | 7539.25 | 2314.78 | 619.20 | 36.66 | 7.75 | 0.98 | 0.00 | 0.00 | 0.00 |
| OC | 8866.20 | 7539.25 | 2314.78 | 619.20 | 36.66 | 7.75 | 0.98 | 0.00 | 0.00 | 0.00 |
| OD | 8866.20 | 7539.25 | 2314.78 | 619.20 | 36.66 | 7.75 | 0.98 | 0.00 | 0.00 | 0.00 |



| H[m] | D[m] | Max lux | Med lux | Alpha=10.0°+10.0° | G=0.0 |
|------|------|---------|---------|-------------------|-------|
| 1.00 | 0.35 | 8866 | 5657 | | |
| 2.00 | 0.70 | 2217 | 1414 | | |
| 3.00 | 1.05 | 985 | 629 | | |
| 4.00 | 1.40 | 554 | 354 | | |
| 5.00 | 1.75 | 355 | 226 | | |