


Luminaire

Code AP05215+AP90200
 Name VECTOR 40 MAGNET 940 FL DALI BR.SILVER + LENS FOR ELLIPTICAL EMISSION

Measurement

Code FTS1800551
 Name VECTOR 40 MAGNET 940 FL DALI BR.SILVER + LENS FOR ELLIPTICAL EMISSION

| | | | | | | | |
|--|-------------------|-----------------|----------------|-----------------------------|---------------|--------------------|--------------------|
| Luminaire Flux | 356 lm | Luminaire Power | 9.0 W | Efficacy | 39.527 lm/W | Efficiency | 100.00% |
| Source Flux | 356 lm | Maximum value | 3396.08 cd/klm | Position | C=0.00 G=0.00 | CG | Double Symmetrical |
| Round Luminaire | | Diam. | 40 mm | Height | 103 mm | | |
| Round Luminous Area | | Diam. | 27 mm | Height | 0 mm | | |
| Horizontal Luminous Area | | | 0.000573 m2 | Emitting area on Plane 180° | | | 0.000000 m2 |
| Emitting area on Plane 0° | | | 0.000000 m2 | Emitting area on Plane 270° | | | 0.000000 m2 |
| Emitting area on Plane 90° | | | 0.000000 m2 | Glare area at 76° | | | 0.000139 m2 |
| Coordinate system | | CG | | Symmetry Type | | Double Symmetrical | |
| Date | | 23-09-2021 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 356 lm | |
| LED Flux=907lm LED Power=8W Eff=39% EfcLed=113lm/W EfcLum=40lm/W CCT=4000K Ra=90 SDCM=2 L70(6K)=50000h | | | | | | | |
| C.I.E. | 96 99 100 100 100 | | | D DIN 5040 | A60 | | |
| F UTE | 1.00 A | | | B NBN | BZ 1 | | |



Luminaire

Code AP05215+AP90200
Name VECTOR 40 MAGNET 940 FL DALI BR.SILVER + LENS FOR ELLIPTICAL EMISSION

Measurment.


Code FTS1800551
Name VECTOR 40 MAGNET 940 FL DALI BR.SILVER + LENS FOR ELLIPTICAL EMISSION

| | | | | | | | |
|--|-------------------|-----------------|----------------|-----------------------------|---------------|--------------------|--------------------|
| Luminaire Flux | 356 lm | Luminaire Power | 9.0 W | Efficacy | 39.527 lm/W | Efficiency | 100.00% |
| Source Flux | 356 lm | Maximum value | 3396.08 cd/klm | Position | C=0.00 G=0.00 | CG | Double Symmetrical |
| Round Luminaire | | Diam. | 40 mm | Height | 103 mm | | |
| Round Luminous Area | | Diam. | 27 mm | Height | 0 mm | | |
| Horizontal Luminous Area | | 0.000573 m2 | | Emitting area on Plane 180° | | 0.000000 m2 | |
| Emitting area on Plane 0° | | 0.000000 m2 | | Emitting area on Plane 270° | | 0.000000 m2 | |
| Emitting area on Plane 90° | | 0.000000 m2 | | Glare area at 76° | | 0.000139 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Double Symmetrical | |
| Date | | 23-09-2021 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 356 lm | |
| LED Flux=907lm LED Power=8W Eff=39% EfcLed=113lm/W EfcLum=40lm/W CCT=4000K Ra=90 SDCM=2 L70(6K)=50000h | | | | | | | |
| C.I.E. | 96 99 100 100 100 | | | D DIN 5040 | A60 | | |
| F UTE | 1.00 A | | | B NBN | BZ 1 | | |

Width at 50.00 % of Max Intensity

| H[m] | 1.00 | 2.00 | 3.00 | 4.00 | 5.00 | H[m] | 1.00 | 2.00 | 3.00 | 4.00 | 5.00 |
|------|------|------|------|------|------|------|------|------|------|------|------|
| OA | 0.19 | 0.37 | 0.56 | 0.74 | 0.93 | OC | 0.32 | 0.64 | 0.96 | 1.28 | 1.60 |
| OB | 0.19 | 0.37 | 0.56 | 0.74 | 0.93 | OD | 0.32 | 0.64 | 0.96 | 1.28 | 1.60 |

| | Luminous Intensities [cd/klm] | | | | | | | | | |
|----|---------------------------------|---------|--------|--------|--------|-------|-------|-------|------|------|
| | 0 | 5 | 15 | 25 | 35 | 45 | 55 | 65 | 75 | 85 |
| OA | 1208.12 | 1022.27 | 331.35 | 76.17 | 12.17 | 4.26 | 2.10 | 1.32 | 0.85 | 0.29 |
| OB | 1208.12 | 1022.27 | 331.35 | 76.17 | 12.17 | 4.26 | 2.10 | 1.32 | 0.85 | 0.29 |
| OC | 1208.12 | 1132.64 | 726.25 | 340.06 | 117.40 | 29.16 | 14.95 | 10.05 | 2.19 | 0.28 |
| OD | 1208.12 | 1132.64 | 726.25 | 340.06 | 117.40 | 29.16 | 14.95 | 10.05 | 2.19 | 0.28 |



| H[m] | D[m] | Max lux | Med lux | Alpha=10.5°+10.5° | G=0.0 |
|------|------|---------|---------|-------------------|-------|
| 1.00 | 0.37 | 1208 | 732 | | |
| 2.00 | 0.74 | 302 | 183 | | |
| 3.00 | 1.11 | 134 | 81 | | |
| 4.00 | 1.48 | 76 | 46 | | |
| 5.00 | 1.85 | 48 | 29 | | |

| H[m] | D[m] | Max lux | Med lux | Beta=17.8°+17.8° | G=0.0 |
|------|------|---------|---------|------------------|-------|
| 1.00 | 0.64 | 1208 | 732 | | |
| 2.00 | 1.28 | 302 | 183 | | |
| 3.00 | 1.93 | 134 | 81 | | |
| 4.00 | 2.57 | 76 | 46 | | |
| 5.00 | 3.21 | 48 | 29 | | |