


Luminaire

Code AP21218+AP90400
Name VECTOR 40 MAGNET SUSP 927 FL BCP + ANTI DAZZLE LOUVRE

Measurement

Code FTS2001294
Name VECTOR 40 MAGNET SUSP 927 FL BCP + ANTI DAZZLE LOUVRE

Luminaire Flux	279 lm	Luminaire Power	9.0 W	Efficacy	30.991 lm/W	Efficiency	100.00%
Source Flux	279 lm	Maximum value	6075.95 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	40 mm	Height	103 mm		
Round Luminous Area		Diam.	27 mm	Height	0 mm		
Horizontal Luminous Area		0.000573 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000139 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		23-09-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		279 lm	
LED Flux=786lm LED Power=8W Eff=35% EfcLed=98lm/W EfcLum=31lm/W CCT=2700K Ra=90 SDCM=2 L70(6K)=50000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1



Luminaire

Code AP21218+AP90400
Name VECTOR 40 MAGNET SUSP 927 FL BCP + ANTI DAZZLE LOUVRE

Measur.


Code FTS2001294
Name VECTOR 40 MAGNET SUSP 927 FL BCP + ANTI DAZZLE LOUVRE

Luminaire Flux	279 lm	Luminaire Power	9.0 W	Efficacy	30.991 lm/W	Efficiency	100.00%
Source Flux	279 lm	Maximum value	6075.95 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	40 mm	Height	103 mm		
Round Luminous Area		Diam.	27 mm	Height	0 mm		
Horizontal Luminous Area		0.000573 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000139 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		23-09-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		279 lm	
LED Flux=786lm LED Power=8W Eff=35% EfcLed=98lm/W EfcLum=31lm/W CCT=2700K Ra=90 SDCM=2 L70(6K)=50000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.18	0.36	0.54	0.72	0.90	OC	0.18	0.36	0.54	0.72	0.90
OB	0.18	0.36	0.54	0.72	0.90	OD	0.18	0.36	0.54	0.72	0.90

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1694.70	1418.65	402.62	75.92	9.67	2.27	0.64	0.24	0.20	0.17
OB	1694.70	1418.65	402.62	75.92	9.67	2.27	0.64	0.24	0.20	0.17
OC	1694.70	1418.65	402.62	75.92	9.67	2.27	0.64	0.24	0.20	0.17
OD	1694.70	1418.65	402.62	75.92	9.67	2.27	0.64	0.24	0.20	0.17



H[m]	D[m]	Max lux	Med lux	Alpha=10.2°+10.2°	G=0.0
1.00	0.36	1695	1067		
2.00	0.72	424	267		
3.00	1.08	188	119		
4.00	1.43	106	67		
5.00	1.79	68	43		