

Luminaire

Code BH21001+BH16104
 Name A.39 RCS TRIM SHARP 1184 HB S 930 BCO + 3X4 OPT. HB BLACK

Measurem.

Code FTS1900601
 Name A.39 RCS TRIM SHARP 1184 HB S 930 BCO + 3X4 OPT. HB BLACK

| | | | | | | | |
|----------------------------------------------------------------------------------------------------|------------|-------------------------|----------------|-----------------------------|---------------|-------------------------|-----------------|
| Luminaire Flux | 2433.06 lm | Luminaire Power | 33.00 W | Efficacy | 73.73 lm/W | Efficiency | 100.00% |
| Sources Flux | 2433.06 lm | Maximum value | 5604.42 cd/klm | Position | C=0.00 G=0.00 | CG | Rotosymmetrical |
| Rectangular Luminaire | | Length | 1184 mm | Width | 40 mm | Height | 111 mm |
| Rectangular Luminous Area | | Length | 444 mm | Width | 37 mm | Height | 0 mm |
| Horizontal Luminous Area | | 0.016428 m ² | | Emitting area on Plane 180° | | 0.000000 m ² | |
| Emitting area on Plane 0° | | 0.000000 m ² | | Emitting area on Plane 270° | | 0.000000 m ² | |
| Emitting area on Plane 90° | | 0.000000 m ² | | Glare area at 76° | | 0.003974 m ² | |
| Coordinate system | | CG | | Symmetry Type | | Rotosymmetrical | |
| Date | | 21-02-2017 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 2433.06 lm | |
| LED Flux=3264,55lm LED Power=33W Eff=75% EfcLed=99lm/W EfcLum=74lm/W Ra=90 SDCM=2 L90(20K)=118000h | | | | | | | |
| C.I.E. | 100 | 100 | 100 | 100 | 100 | D DIN 5040 | A60 |
| F UTE | -- | | | | | B NBN | BZ 1 |

1184mm x 40mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
 DLOR 100.00 %
 RN 0.00 %



