

## Luminaire


Code BH22304+BH16204  
 Name A.39 RCS TRIM SHARP 2368 LB F 940 NRO + 4X4 OPT. LB BLACK

## Measurement

Code FTS1900641  
 Name A.39 RCS TRIM SHARP 2368 LB F 940 NRO + 4X4 OPT. LB BLACK

Luminaire Flux	3260.74 lm	Luminaire Power	44.00 W	Efficacy	74.11 lm/W	Efficiency	100.00%
Sources Flux	3260.74 lm	Maximum value	2630.91 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire	Length	2368 mm	Width	40 mm	Height	111 mm	
Rectangular Luminous Area	Length	592 mm	Width	37 mm	Height	0 mm	
Horizontal Luminous Area	0.021904 m <sup>2</sup>	Emitting area on Plane 180°	0.000000 m <sup>2</sup>	Emitting area on Plane 270°	0.000000 m <sup>2</sup>	Emitting area on Plane 90°	0.005299 m <sup>2</sup>
Coordinate system	CG	Symmetry Type	Rotosymmetrical		Maximum Gamma Angle	180	
Date	16-02-2017	Measurement Flux	3260.74 lm				
Measurement Distance	0.00						
LED Flux=4658,2lm LED Power=44W Eff=70% EfcLed=106lm/W EfcLum=74lm/W Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	99 100 100 100 100	D DIN 5040	A60				
F UTE	--	B NBN	BZ 1				


2368mm x 40mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %  
 DLOR 100.00 %  
 RN 0.00 %



## Luminaire

Code BH22304+BH16204  
 Name A.39 RCS TRIM SHARP 2368 LB F 940 NRO + 4X4 OPT. LB BLACK

## Measurem.


Code FTS1900641  
 Name A.39 RCS TRIM SHARP 2368 LB F 940 NRO + 4X4 OPT. LB BLACK

Luminaire Flux	3260.74 lm	Luminaire Power	44.00 W	Efficacy	74.11 lm/W	Efficiency	100.00%
Sources Flux	3260.74 lm	Maximum value	2630.91 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	592 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.021904 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.005299 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		16-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3260.74 lm	
LED Flux=4658,2lm LED Power=44W Eff=70% EfcLed=106lm/W EfcLum=74lm/W Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.33	0.65	0.98	1.30	1.63	OC	0.33	0.65	0.98	1.30	1.63
OB	0.33	0.65	0.98	1.30	1.63	OD	0.33	0.65	0.98	1.30	1.63

	Luminous Intensities [ cd/klm ]									
	0	5	15	25	35	45	55	65	75	85
OA	8578.70	7969.20	5240.27	1868.14	317.61	63.98	7.52	1.04	0.00	0.00
OB	8578.70	7969.20	5240.27	1868.14	317.61	63.98	7.52	1.04	0.00	0.00
OC	8578.70	7969.20	5240.27	1868.14	317.61	63.98	7.52	1.04	0.00	0.00
OD	8578.70	7969.20	5240.27	1868.14	317.61	63.98	7.52	1.04	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=18.0°+18.0°	G=0.0
1.00	0.65	8579	4989		
2.00	1.30	2145	1247		
3.00	1.95	953	554		
4.00	2.60	536	312		
5.00	3.25	343	200		