

Luminaire

Code BH04905+BH16004
 Name A.39 S/C SHAR DIR 1184 LB 54 400K ND SIL + COVER 2X4 OPT. LB BLACK

Measurement

Code FTS1900031
 Name A.39 S/C SHAR DIR 1184 LB 54 400K ND SIL + COVER 2X4 OPT. LB BLACK

Luminaire Flux	1668.56 lm	Luminaire Power	27.00 W	Efficacy	61.80 lm/W	Efficiency	100.00%
Sources Flux	1668.56 lm	Maximum value	1430.97 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	1184 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	296 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.010952 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.002650 m ²	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		17-07-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1668.56 lm	


LED Flux=2329,1lm LED Power=22W Eff=72% EfcLed=106lm/W EfcLum=62lm/W Ra=90 SDCM=2 L90(20K)=118000h

C.I.E. 99 100 100 100 100
 F UTE --

D DIN 5040
 B NBN

A60
 BZ 1


1184mm x 40mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
 DLOR 100.00 %
 RN 0.00 %



Luminaire

Code BH04905+BH16004
 Name A.39 S/C SHAR DIR 1184 LB 54 400K ND SIL + COVER 2X4 OPT. LB BLACK

Measurerm.

Code FTS1900031
 Name A.39 S/C SHAR DIR 1184 LB 54 400K ND SIL + COVER 2X4 OPT. LB BLACK

Luminaire Flux	1668.56 lm	Luminaire Power	27.00 W	Efficacy	61.80 lm/W	Efficiency	100.00%
Sources Flux	1668.56 lm	Maximum value	1430.97 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	1184 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	296 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.010952 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.002650 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		17-07-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1668.56 lm	


LED Flux=2329,1lm LED Power=22W Eff=72% EfcLed=106lm/W EfcLum=62lm/W Ra=90 SDCM=2 L90(20K)=118000h

C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.49	0.98	1.47	1.96	2.44	OC	0.49	0.98	1.47	1.96	2.44
OB	0.49	0.98	1.47	1.96	2.44	OD	0.49	0.98	1.47	1.96	2.44

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	2387.65	2370.49	2164.42	1439.70	254.92	37.18	2.90	0.00	0.00	0.00
OB	2387.65	2370.49	2164.42	1439.70	254.92	37.18	2.90	0.00	0.00	0.00
OC	2387.65	2370.49	2164.42	1439.70	254.92	37.18	2.90	0.00	0.00	0.00
OD	2387.65	2370.49	2164.42	1439.70	254.92	37.18	2.90	0.00	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=26.1°+26.1°	G=0.0	
1.00	0.98	2388	1441			
2.00	1.96	597	360			
3.00	2.93	265	160			
4.00	3.91	149	90			
5.00	4.89	96	58			