

Luminaire

Code BH12401+BH16001
 Name A.39 SHARP D+IND 1184 LB 34 300K ND BCO + COVER 2X4 OPT. LB WHITE

Measurement

Code FTS1900331-A
 Name A.39 SHARP D+IND 1184 LB 34 300K ND BCO + COVER 2X4 OPT. LB WHITE

Luminaire Flux	4617 lm	Luminaire Power	53.0 W	Efficacy	87.113 lm/W	Efficiency	100.00%
Source Flux	4617 lm	Maximum value	858.73 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1184 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	296 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.010952 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.002650 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		21-11-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4617 lm	
LED Flux=5884lm LED Power=42W Eff=78% EfcLed=140lm/W EfcLum=87lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h							
C.I.E.	97 99 100 33 100			D DIN 5040		D62	
F UTE	--			B NBN		BZ 1	



