

Luminaire


Code BH12504+BH16004
 Name A.39 SHARP D+IND 1184 LB 34 400K ND NRO + COVER 2X4 OPT. LB BLACK

Measurem.

Code FTS1900061
 Name A.39 SHARP D+IND 1184 LB 34 400K ND NRO + COVER 2X4 OPT. LB BLACK

Luminaire Flux	4718.84 lm	Luminaire Power	53.00 W	Efficacy	89.03 lm/W	Efficiency	100.00%
Sources Flux	4718.84 lm	Maximum value	908.98 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1184 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	296 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.010952 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.002650 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		16-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4718.84 lm	
LED Flux=5957,9lm LED Power=44W Eff=79% EfcLed=135lm/W EfcLum=89lm/W Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	99	100	100	35	100	D DIN 5040	D62
F UTE	--					B NBN	BZ 1

1184mm x 40mm



Semipiani C

180.0 ——— 0.0
 270.0 ——— 90.0

ULOR 65.45 %
 DLOR 34.55 %
 RN 65.45 %

