

## Luminaire

Code BH12505+BH16004  
 Name A.39 SHARP D+IND 1184 LB 34 400K ND SIL + COVER 2X4 OPT. LB BLACK

## Measurem.

Code FTS1900061  
 Name A.39 SHARP D+IND 1184 LB 34 400K ND SIL + COVER 2X4 OPT. LB BLACK


Luminaire Flux	4718.84 lm	Luminaire Power	53.00 W	Efficacy	89.03 lm/W	Efficiency	100.00%
Sources Flux	4718.84 lm	Maximum value	908.98 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1184 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	296 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.010952 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.002650 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		16-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4718.84 lm	

LED Flux=5957,9lm LED Power=44W Eff=79% EfcLed=135lm/W EfcLum=89lm/W Ra=90 SDCM=2 L90(20K)=118000h

C.I.E. 99 100 100 35 100  
 F UTE --

D DIN 5040  
 B NBN  
 D62  
 BZ 1

1184mm x 40mm



Semipiani C

180.0 — 0.0  
 270.0 — 90.0

ULOR 65.45 %

DLOR 34.55 %

RN 65.45 %

