

Luminaire

Code BH10405+BH16304
 Name A.39 SHARP D+IND 2368 HB 34 300K ND SIL + COVER 6X4 OPT. HB BLACK

Measurem.

Code FTS1900259-B
 Name A.39 SHARP D+IND 2368 HB 34 300K ND SIL + COVER 6X4 OPT. HB BLACK

Luminaire Flux	10720 lm	Luminaire Power	125.0 W	Efficacy	85.760 lm/W	Efficiency	100.00%
Source Flux	10720 lm	Maximum value	1121.62 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	888 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.032856 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.007949 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		21-11-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		10720 lm	
LED Flux=13945lm LED Power=107W Eff=77% EfcLed=130lm/W EfcLum=86lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h							
C.I.E.	99 100 100 43 100			D DIN 5040	C62		
F UTE	--			B NBN	BZ 1		



