

Luminaire

Code BH09004+BH16101
 Name A.39 SHARP D+IND 1184 HB 54 300K DM NRO + COVER 3X4 OPT. HB WHITE

Measurement

Code FTS1900409-A
 Name A.39 SHARP D+IND 1184 HB 54 300K DM NRO + COVER 3X4 OPT. HB WHITE

Luminaire Flux	5471 lm	Luminaire Power	64.0 W	Efficacy	85.484 lm/W	Efficiency	100.00%
Source Flux	5471 lm	Maximum value	615.89 cd/klm	Position	C=0.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1184 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	444 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.016428 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.003974 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		21-11-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		5471 lm	


LED Flux=6973lm LED Power=53W Eff=78% EfcLed=132lm/W EfcLum=85lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h

C.I.E. 97 99 100 44 100
 F UTE --

D DIN 5040
 B NBN

C62
 BZ 1

1184mm x 40mm



Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 56.20 %
 DLOR 43.80 %
 RN 56.20 %

