

## Luminaire

Code BH08704+BH16104  
 Name A.39 SHARP D+IND 1184 HB 34 400K DM NRO + COVER 3X4 OPT. HB BLACK

## Measurement

Code FTS1900133  
 Name A.39 SHARP D+IND 1184 HB 34 400K DM NRO + COVER 3X4 OPT. HB BLACK

Luminaire Flux	5534.03 lm	Luminaire Power	64.00 W	Efficacy	86.47 lm/W	Efficiency	100.00%
Sources Flux	5534.03 lm	Maximum value	1162.63 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1184 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	444 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.016428 m <sup>2</sup>		Emitting area on Plane 180°		0.000000 m <sup>2</sup>	
Emitting area on Plane 0°		0.000000 m <sup>2</sup>		Emitting area on Plane 270°		0.000000 m <sup>2</sup>	
Emitting area on Plane 90°		0.000000 m <sup>2</sup>		Glare area at 76°		0.003974 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		16-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		5534.03 lm	
LED Flux=7122,45lm LED Power=55W Eff=78% EfcLed=129lm/W EfcLum=86lm/W Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	99 100 100 44 100			D DIN 5040		C62	
F UTE	--			B NBN		BZ 1	



