

Luminaire

Code BH10305+BH16301
 Name A.39 SHARP D+IND 2368 HB 17 400K DM SIL + COVER 6X4 OPT. HB WHITE

Measurem.

Code FTS1900562
 Name A.39 SHARP D+IND 2368 HB 17 400K DM SIL + COVER 6X4 OPT. HB WHITE


| | | | | | | | |
|----------------------------|-------------|-----------------|----------------|-----------------------------|---------------|--------------------|--------------------|
| Luminaire Flux | 11469.40 lm | Luminaire Power | 120.00 W | Efficacy | 95.58 lm/W | Efficiency | 100.00% |
| Sources Flux | 11469.40 lm | Maximum value | 2557.10 cd/klm | Position | C=0.00 G=0.00 | CG | Double Symmetrical |
| Rectangular Luminaire | | Length | 2368 mm | Width | 40 mm | Height | 111 mm |
| Rectangular Luminous Area | | Length | 888 mm | Width | 37 mm | Height | 0 mm |
| Horizontal Luminous Area | | 0.032856 m2 | | Emitting area on Plane 180° | | 0.000000 m2 | |
| Emitting area on Plane 0° | | 0.000000 m2 | | Emitting area on Plane 270° | | 0.000000 m2 | |
| Emitting area on Plane 90° | | 0.000000 m2 | | Glare area at 76° | | 0.007949 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Double Symmetrical | |
| Date | | 21-02-2017 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 11469.40 lm | |

LED Flux=14244,9lm LED Power=103W Eff=81% EfcLed=138lm/W EfcLum=96lm/W Ra=90 SDCM=2 L90(20K)=118000h

C.I.E. 99 100 100 46 100
 F UTE --

D DIN 5040
 B NBN
 C62
 BZ 1

2368mm x 40mm



Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 53.85 %
 DLOR 46.15 %
 RN 53.85 %

