

## Luminaire


Code M2882N00+M196900  
 Name ALGORITMO SYSTEM PIASTRA CABLATA DIRETTA LED 4000K NON DIMMERABILE 1184MM+OTTICA PRISMOPTIC 1184MM PER LED

## Measurement

Code FTS1601402  
 Name ALGORITMO SYSTEM PIASTRA CABLATA DIRETTA LED 4000K NON DIMMERABILE 1184MM+OTTICA PRISMOPTIC 1184MM PER LED

Luminaire Flux	2646 lm	Luminaire Power	34.0 W	Efficacy	77.821 lm/W	Efficiency	100.00%
Source Flux	2646 lm	Maximum value	470.35 cd/klm	Position	C=90.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1185 mm	Width	45 mm	Height	110 mm
Rectangular Luminous Area		Length	1185 mm	Width	32 mm	Height	0 mm
Horizontal Luminous Area		0.037920 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.009174 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		24-06-2016		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2646 lm	
LED Flux=4561,92lm LED Power=27W Eff=58% EfcLed=169lm/W EfcLum=78lm/W Ra=80 SDCM=3 L70(6K)=50000h							
C.I.E.	57 86 97 99 100			D DIN 5040	A41		
F UTE	0.99 D + 0.01 T			B NBN	BZ 3		

1185mm x 45mm



Semipiani C

180.0 ——— 0.0  
 270.0 ——— 90.0

ULOR 0.65 %  
 DLOR 99.35 %  
 RN 0.65 %

