

Luminaire

Code 2110010AHE
Name AOL SYSTEM S LIN.180 SLV TER 3000K HE

Measurement

Code FTS2400057
Name AOL SYSTEM S LIN.180 SLV TER 3000K HE

Luminaire Flux	3400 lm	Luminaire Power	33.0 W	Efficacy	103.030 lm/W	Efficiency	100.00%
Source Flux	3400 lm	Maximum value	156.12 cd/klm	Position	C=5.00 G=5.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1800 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area		Length	1800 mm	Width	50 mm	Height	50 mm
Horizontal Luminous Area		0.090000 m2		Emitting area on Plane 180°		0.090000 m2	
Emitting area on Plane 0°		0.090000 m2		Emitting area on Plane 270°		0.002500 m2	
Emitting area on Plane 90°		0.002500 m2		Glare area at 76°		0.109100 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		26-03-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3400 lm	


LED Flux=4262lm LED Power=33W Eff=80% EfcLed=129lm/W EfcLum=103lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(10k)=60000h

C.I.E. 33 60 82 69 100
F UTE 0.69 H + 0.31 T

D DIN 5040
B NBN

B21
BZ 6

1800mm x 50mm



Semipiani C

180.0 ——— 0.0
270.0 ——— 90.0

ULOR 31.35 %

DLOR 68.65 %

RN 31.35 %

