

## Luminaire

Code 2121010AHE  
Name AOL SYSTEM S 60° SLV TER SX 3000K HE

## Measurement

Code FTS2400059  
Name AOL SYSTEM S 60° SLV TER SX 3000K HE

Luminaire Flux	815 lm	Luminaire Power	8.0 W	Efficacy	101.875 lm/W	Efficiency	100.00%
Source Flux	815 lm	Maximum value	162.58 cd/klm	Position	C=20.00 G=5.00	CG	Sym. on planes 0-180
Rectangular Luminaire		Length	475 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area		Length	475 mm	Width	50 mm	Height	50 mm
Horizontal Luminous Area		0.023750 m <sup>2</sup>		Emitting area on Plane 180°		0.023750 m <sup>2</sup>	
Emitting area on Plane 0°		0.023750 m <sup>2</sup>		Emitting area on Plane 270°		0.002500 m <sup>2</sup>	
Emitting area on Plane 90°		0.002500 m <sup>2</sup>		Glare area at 76°		0.028790 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Sym. on planes 0-180	
Date		26-03-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		815 lm	


LED Flux=1066lm LED Power=8W Eff=76% EfcLed=133lm/W EfcLum=102lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(10k)=60000h

C.I.E. 33 61 83 70 100  
F UTE 0.70 H + 0.30 T

D DIN 5040  
B NBN

B21  
BZ 6

475mm x 50mm



Semipiani C

180.0 — 0.0  
270.0 — 90.0

ULOR 30.45 %

DLOR 69.55 %

RN 30.45 %

