


## Luminaire

Code 2000010A\_N  
Name DISCOVERY SPACE 90x90 S TW - COLD


## Measurem.

Code FTS2000457-B  
Name DISCOVERY SPACE 90x90 S TW - COLD

Luminaire Flux	2739 lm	Luminaire Power	44.0 W	Efficacy	62.250 lm/W	Efficiency	100.00%
Source Flux	2739 lm	Maximum value	154.54 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	970 mm	Width	970 mm	Height	17 mm
Rectangular Luminous Area		Length	900 mm	Width	900 mm	Height	10 mm
Horizontal Luminous Area		0.810000 m <sup>2</sup>		Emitting area on Plane 180°		0.009000 m <sup>2</sup>	
Emitting area on Plane 0°		0.009000 m <sup>2</sup>		Emitting area on Plane 270°		0.009000 m <sup>2</sup>	
Emitting area on Plane 90°		0.009000 m <sup>2</sup>		Glare area at 76°		0.204689 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		14-10-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2739 lm	
LED Flux=4740lm LED Power=37W Eff=58% EfcLed=128lm/W EfcLum=62lm/W CCT=6500K Ra=80 L70(6K)=60000h							
C.I.E.	42 72 92 51 100			D DIN 5040		C31	
F UTE	0.51 G + 0.49 T			B NBN		BZ 5	



ULOR 48.78 %  
DLOR 51.22 %  
RN 48.78 %



## Luminaire

Code 2000010A\_N  
Name DISCOVERY SPACE 90x90 S TW - COLD

## Measurment

Code FTS2000457-B  
Name DISCOVERY SPACE 90x90 S TW - COLD

Luminaire Flux	2739 lm	Luminaire Power	44.0 W	Efficacy	62.250 lm/W	Efficiency	100.00%
Source Flux	2739 lm	Maximum value	154.54 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	970 mm	Width	970 mm	Height	17 mm
Rectangular Luminous Area		Length	900 mm	Width	900 mm	Height	10 mm
Horizontal Luminous Area		0.810000 m2		Emitting area on Plane 180°		0.009000 m2	
Emitting area on Plane 0°		0.009000 m2		Emitting area on Plane 270°		0.009000 m2	
Emitting area on Plane 90°		0.009000 m2		Glare area at 76°		0.204689 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		14-10-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2739 lm	


LED Flux=4740lm LED Power=37W Eff=58% EfcLed=128lm/W EfcLum=62lm/W CCT=6500K Ra=80 L70(6K)=60000h

C.I.E.	42 72 92 51 100	D DIN 5040	C31
F UTE	0.51 G + 0.49 T	B NBN	BZ 5

### Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	2.00	4.01	6.01	8.02	10.02	OC	1.89	3.78	5.68	7.57	9.46
OB	2.00	4.01	6.01	8.02	10.02	OD	1.89	3.78	5.68	7.57	9.46

	Luminous Intensities [ cd/klm ]									
	0	5	15	25	35	45	55	65	75	85
OA	423.28	421.88	408.18	381.41	345.50	303.55	256.04	203.26	141.40	75.25
OB	423.28	421.88	408.18	381.41	345.50	303.55	256.04	203.26	141.40	75.25
OC	423.28	421.85	409.10	385.37	351.04	307.92	254.40	193.52	123.59	50.22
OD	423.28	421.85	409.10	385.37	351.04	307.92	254.40	193.52	123.59	50.22



H[m]	D[m]	Max lux	Med lux	Alpha=63.5°+63.5°	G=0.0
1.00	4.01	423	73		
2.00	8.02	106	18		
3.00	12.03	47	8		
4.00	16.04	26	5		
5.00	20.05	17	3		

H[m]	D[m]	Max lux	Med lux	Beta=62.1°+62.1°	G=0.0
1.00	3.78	423	73		
2.00	7.57	106	18		
3.00	11.35	47	8		
4.00	15.14	26	5		
5.00	18.92	17	3		