

## Luminaire

Code AQ75518  
Name A.24 SOSP 360 1500 SHARP FL2700 BCP

## Measurement

Code FTS1901642  
Name A.24 SOSP 360 1500 SHARP FL2700 BCP

Luminaire Flux	6112 lm	Luminaire Power	83.0 W	Efficacy	73.644 lm/W	Efficiency	100.00%
Source Flux	6112 lm	Maximum value	2814.46 cd/klm	Position	C=20.00 G=1.00	CG	Double Symmetrical
Round Luminaire		Diam.	1550 mm	Height	54 mm		
Round Luminous Area		Diam.	124 mm	Height	0 mm		
Horizontal Luminous Area			0.012076 m2	Emitting area on Plane 180°			0.000000 m2
Emitting area on Plane 0°			0.000000 m2	Emitting area on Plane 270°			0.000000 m2
Emitting area on Plane 90°			0.000000 m2	Glare area at 76°			0.002922 m2
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		21-11-2018		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		6112 lm	
LED Flux=7509.2lm LED Power=76W Eff=81% EfcLed=99lm/W EfcLum=74lm/W CCT=2700K Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	98	100	100	100	D DIN 5040	A60	
F UTE	--				B NBN	BZ 1	



