

Luminaire

Code AF15705
Name SHARP RCS.TRIM.8X 22W 930 WW SIL/NRO

Measurerm.

Code FTS2000137
Name SHARP RCS.TRIM.8X 22W 930 WW SIL/NRO

Luminaire Flux	1312.91 lm	Luminaire Power	22.00 W	Efficacy	59.68 lm/W	Efficiency	100.00%
Lamps Flux	1312.91 lm	Maximum value	1103.17 cd/klm	Position	C=175.00 G=9.00	CG	Sym. on planes 0-180
Rectangular Luminaire		Length	300 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	290 mm	Width	32 mm	Height	0 mm
Horizontal Luminous Area	0.009280 m2			Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°	0.000000 m2			Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°	0.000000 m2			Glare area at 76°		0.002245 m2	
Coordinate system	CG			Symmetry Type		Sym. on planes 0-180	
Date	29-10-2019			Maximum Gamma Angle		180	
Measurement Distance	0.00			Measurement Flux		1312.91 lm	


LED Flux=2186lm LED Power=22W Eff=60% EfcLed=99lm/W EfcLum=60lm/W CCT=3000K Ra=90 SDCM=2 L90(20K)=118000h

C.I.E. 73 92 98 100 100
F UTE 1.00 B

D DIN 5040
B NBN

A60
BZ 1 / 1 / BZ 2

300mm x 45mm



Semipiani C

180.0 ——— 0.0
270.0 ——— 90.0

ULOR 0.18 %
DLOR 99.82 %
RN 0.18 %

