

## Luminaire

Code AF75704  
Name SHARP.RCS.TLESS.16X 44W 930 WW RIFL.NRO

## Measurem.

Code FTS2000174  
Name SHARP.RCS.TLESS.16X 44W 930 WW RIFL.NRO

|                            |            |                 |                |                             |                 |                      |                      |
|----------------------------|------------|-----------------|----------------|-----------------------------|-----------------|----------------------|----------------------|
| Luminaire Flux             | 2625.82 lm | Luminaire Power | 44.00 W        | Efficacy                    | 59.68 lm/W      | Efficiency           | 100.00%              |
| Lamps Flux                 | 2625.82 lm | Maximum value   | 1103.17 cd/klm | Position                    | C=175.00 G=9.00 | CG                   | Sym. on planes 0-180 |
| Rectangular Luminaire      |            | Length          | 600 mm         | Width                       | 45 mm           | Height               | 85 mm                |
| Rectangular Luminous Area  |            | Length          | 590 mm         | Width                       | 32 mm           | Height               | 0 mm                 |
| Horizontal Luminous Area   |            |                 | 0.018880 m2    | Emitting area on Plane 180° |                 |                      | 0.000000 m2          |
| Emitting area on Plane 0°  |            |                 | 0.000000 m2    | Emitting area on Plane 270° |                 |                      | 0.000000 m2          |
| Emitting area on Plane 90° |            |                 | 0.000000 m2    | Glare area at 76°           |                 |                      | 0.004567 m2          |
| Coordinate system          |            | CG              |                | Symmetry Type               |                 | Sym. on planes 0-180 |                      |
| Date                       |            | 29-10-2019      |                | Maximum Gamma Angle         |                 | 180                  |                      |
| Measurement Distance       |            | 0.00            |                | Measurement Flux            |                 | 2625.82 lm           |                      |

LED Flux=4372lm LED Power=44W Eff=60% EfcLed=99lm/W EfcLum=60lm/W CCT=3000K Ra=90 SDCM=2 L90(20K)=118000h

C.I.E. 73 92 98 100 100  
F UTE 1.00 B

D DIN 5040  
B NBN

A60  
BZ 1 / 1 / BZ 2



