

Luminaire

Code AF86654
Name SHARP SMD.16X 44W 927 WW ND BCO/NRO

Measurement

Code FTS1903541-A
Name SHARP SMD.16X 44W 927 WW ND BCO/NRO

Luminaire Flux	2497 lm	Luminaire Power	47.0 W	Efficacy	53.124 lm/W	Efficiency	100.00%
Source Flux	2497 lm	Maximum value	1103.17 cd/klm	Position	C=175.00 G=9.00	CG	Sym. on planes 0-180
Rectangular Luminaire		Length	600 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	590 mm	Width	32 mm	Height	0 mm
Horizontal Luminous Area		0.018880 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.004567 m2	
Coordinate system		CG		Symmetry Type		Sym. on planes 0-180	
Date		11-11-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2497 lm	


LED Flux=4157lm LED Power=44W Eff=60% EfcLed=94lm/W EfcLum=53lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(6K)=272160h

C.I.E. 73 92 98 100 100
F UTE 1.00 B

D DIN 5040
B NBN

A60
BZ 1 / 1 / BZ 2

600mm x 45mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 0.18 %
DLOR 99.82 %
RN 0.18 %

