

Luminaire


Code AT23601IN0
Name A.39 S D/I CTRL EM 2368 BCO INTEGR WI

Measurerm.

Code FTS2200147
Name A.39 S D/I CTRL EM 2368 BCO INTEGR WI

Luminaire Flux	7622 lm	Luminaire Power	116.0 W	Efficacy	65.711 lm/W	Efficiency	100.00%
Source Flux	7622 lm	Maximum value	234.92 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	45 mm	Height	850 mm
Rectangular Luminous Area		Length	2368 mm	Width	42 mm	Height	0 mm
Horizontal Luminous Area		0.099456 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.024061 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		16-05-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		7622 lm	
LED Flux=12701lm LED Power=95W Eff=60% EfcLed=134lm/W EfcLum=66lm/W CCT=5000K Ra=90 R9=50 SDCM=3 L70(12K)=50000h							
C.I.E.	70 96 99 39 100			D DIN 5040		D52	
F UTE	0.39 C + 0.61 T			B NBN		BZ 2	

2368mm x 45mm



Semipiani C

180.0 ——— 0.0
270.0 ——— 90.0

ULOR 60.77 %

DLOR 39.23 %

RN 60.77 %

