


## Luminaire

Code 1201A00A  
 Name Alphabet of light - A  
**Measurem.**  
 Code FTS1700188-A  
 Name Alphabet of light - A

Luminaire Flux	3060 lm	Luminaire Power	36.0 W	Efficacy	85.006 lm/W	Efficiency	100.00%
Source Flux	3060 lm	Maximum value	114.12 cd/klm	Position	C=90.00 G=89.00	CG	Double Symmetrical
Rectangular Luminaire		Length	50 mm	Width	650 mm	Height	950 mm
Rectangular Luminous Area		Length	50 mm	Width	650 mm	Height	949 mm
Horizontal Luminous Area		0.032500 m <sup>2</sup>		Emitting area on Plane 180°		0.047500 m <sup>2</sup>	
Emitting area on Plane 0°		0.047500 m <sup>2</sup>		Emitting area on Plane 270°		0.617500 m <sup>2</sup>	
Emitting area on Plane 90°		0.617500 m <sup>2</sup>		Glare area at 76°		0.053952 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		10-03-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3060 lm	
LED Flux=3488lm LED Power=36W Eff=88% EfcLed=97lm/W EfcLum=85lm/W CCT=3000K Ra=80 SDCM=3 L70(6K)=36000h							
C.I.E.	21 46 73 50 100			D DIN 5040		C11	
F UTE	0.50 J + 0.50 T			B NBN		BZ 9	

50mm x 650mm



Semipiani C

180.0 ——— 0.0  
 270.0 ——— 90.0

ULOR 50.00 %  
 DLOR 50.00 %  
 RN 50.00 %

