

Luminaire

Code 1202g00A
Name Alphabet of light - g

Measurerm.

Code FTS1700168-A
Name Alphabet of light - g

Luminaire Flux	2502 lm	Luminaire Power	28.0 W	Efficacy	89.364 lm/W	Efficiency	100.00%
Source Flux	2502 lm	Maximum value	114.12 cd/klm	Position	C=90.00 G=89.00	CG	Double Symmetrical
Rectangular Luminaire		Length	50 mm	Width	650 mm	Height	950 mm
Rectangular Luminous Area		Length	50 mm	Width	650 mm	Height	949 mm
Horizontal Luminous Area		0.032500 m ²		Emitting area on Plane 180°		0.047500 m ²	
Emitting area on Plane 0°		0.047500 m ²		Emitting area on Plane 270°		0.617500 m ²	
Emitting area on Plane 90°		0.617500 m ²		Glare area at 76°		0.053952 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		10-03-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2502 lm	


LED Flux=2852lm LED Power=28W Eff=88% EfcLed=102lm/W EfcLum=89lm/W CCT=3000K Ra=80 SDCM=3 L70(6K)=36000h

C.I.E. 21 46 73 50 100
F UTE 0.50 J + 0.50 T

D DIN 5040
B NBN

C11
BZ 9

50mm x 650mm



Semipiani C

180.0 ——— 0.0
270.0 ——— 90.0

ULOR 50.00 %

DLOR 50.00 %

RN 50.00 %

