

Luminaire

Code BB00300+DV1017 + M239700
 Name LUCERI TLESS ROUND.max46W 930 COMFORT + Driver 35W ND + schermo opalino

Measurement

Code FTS1801303
 Name LUCERI TLESS ROUND.max46W 930 COMFORT + Driver 35W ND + schermo opalino

Luminaire Flux	2264.24 lm	Luminaire Power	27.00 W	Efficacy	83.86 lm/W	Efficiency	100.00%
Sources Flux	2264.24 lm	Maximum value	450.72 cd/klm	Position	C=0.00 G=1.00	CG	Rotosymmetrical
Round Luminaire		Diam.	336 mm	Height	260 mm		
Round Luminous Area		Diam.	196 mm	Height	0 mm		
Horizontal Luminous Area		0.030172 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.007299 m ²	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		19-06-2018		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2264.24 lm	
LED Flux=3130lm LED Power=25W Eff=72% EfcLed=125lm/W EfcLum=84lm/W CCT=3000K Ra=90 SDCM=1 L70(6K)=50000h							
C.I.E.	56 86 98 100 100			D DIN 5040	A40		
F UTE	1.00 D			B NBN	BZ 3		

Diam=336mm




Semipiani C

180.0 ——— 0.0

ULOR 0.03 %

DLOR 99.97 %

RN 0.03 %



Luminaire

Code BB00300+DV1017 + M239700
 Name LUCERI TLESS ROUND.max46W 930 COMFORT + Driver 35W ND + schermo opalino

Measurement


Code FTS1801303
 Name LUCERI TLESS ROUND.max46W 930 COMFORT + Driver 35W ND + schermo opalino

Luminaire Flux	2264.24 lm	Luminaire Power	27.00 W	Efficacy	83.86 lm/W	Efficiency	100.00%
Sources Flux	2264.24 lm	Maximum value	450.72 cd/klm	Position	C=0.00 G=1.00	CG	Rotosymmetrical
Round Luminaire		Diam.	336 mm	Height	260 mm		
Round Luminous Area		Diam.	196 mm	Height	0 mm		
Horizontal Luminous Area		0.030172 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.007299 m ²	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		19-06-2018		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2264.24 lm	
LED Flux=3130lm LED Power=25W Eff=72% EfcLed=125lm/W EfcLum=84lm/W CCT=3000K Ra=90 SDCM=1 L70(6K)=50000h							
C.I.E.	56 86 98 100 100			D DIN 5040	A40		
F UTE	1.00 D			B NBN	BZ 3		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	1.08	2.16	3.24	4.31	5.39	OC	1.08	2.16	3.24	4.31	5.39
OB	1.08	2.16	3.24	4.31	5.39	OD	1.08	2.16	3.24	4.31	5.39

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1020.50	1013.82	954.91	848.42	708.46	546.74	378.46	214.02	73.08	10.23
OB	1020.50	1013.82	954.91	848.42	708.46	546.74	378.46	214.02	73.08	10.23
OC	1020.50	1013.82	954.91	848.42	708.46	546.74	378.46	214.02	73.08	10.23
OD	1020.50	1013.82	954.91	848.42	708.46	546.74	378.46	214.02	73.08	10.23



H[m]	D[m]	Max lux	Med lux	Alpha=47.2°+47.2°	G=0.0 Max non a G
1.00	2.16	1021	345		
2.00	4.31	255	86		
3.00	6.47	113	38		
4.00	8.63	64	22		
5.00	10.79	41	14		