

## Luminaire

Code BB10300+DV1018 + M239600  
 Name LUCERI Q TLESS ROUND.max 46W 930 COMFORT + Driver 35W DIM + schermo prismoptic

## Measurem.

Code FTS1801371  
 Name LUCERI Q TLESS ROUND.max 46W 930 COMFORT + Driver 35W DIM + schermo prismoptic


Luminaire Flux	1810.39 lm	Luminaire Power	27.00 W	Efficacy	67.05 lm/W	Efficiency	100.00%
Sources Flux	1810.39 lm	Maximum value	842.43 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	318 mm	Width	318 mm	Height	280 mm
Rectangular Luminous Area		Length	170 mm	Width	170 mm	Height	0 mm
Horizontal Luminous Area		0.028900 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.006992 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		20-06-2018		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1810.39 lm	

LED Flux=3130lm LED Power=25W Eff=58% EfcLed=125lm/W EfcLum=67lm/W CCT=3000K Ra=90 SDCM=1 L70(6K)=50000h


C.I.E. 76 94 99 100 100  
 F UTE 1.00 B

D DIN 5040  
 B NBN

A60  
 BZ 1 / 2.5 / BZ 2



ULOR 0.04 %  
 DLOR 99.96 %  
 RN 0.04 %



## Luminaire

Code BB10300+DV1018 + M239600  
 Name LUCERI Q TLESS ROUND.max 46W 930 COMFORT + Driver 35W DIM + schermo prismoptic

## Measurement

Code FTS1801371  
 Name LUCERI Q TLESS ROUND.max 46W 930 COMFORT + Driver 35W DIM + schermo prismoptic

Luminaire Flux	1810.39 lm	Luminaire Power	27.00 W	Efficacy	67.05 lm/W	Efficiency	100.00%
Sources Flux	1810.39 lm	Maximum value	842.43 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	318 mm	Width	318 mm	Height	280 mm
Rectangular Luminous Area		Length	170 mm	Width	170 mm	Height	0 mm
Horizontal Luminous Area		0.028900 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.006992 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		20-06-2018		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1810.39 lm	


LED Flux=3130lm LED Power=25W Eff=58% EfcLed=125lm/W EfcLum=67lm/W CCT=3000K Ra=90 SDCM=1 L70(6K)=50000h

C.I.E.	76 94 99 100 100	D DIN 5040	A60
F UTE	1.00 B	B NBN	BZ 1 / 2.5 / BZ 2

### Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.58	1.16	1.74	2.33	2.91	OC	0.58	1.16	1.74	2.33	2.91
OB	0.58	1.16	1.74	2.33	2.91	OD	0.58	1.16	1.74	2.33	2.91

	Luminous Intensities [ cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1525.12	1503.22	1300.31	951.20	581.38	269.06	130.39	70.77	29.44	6.97
OB	1525.12	1503.22	1300.31	951.20	581.38	269.06	130.39	70.77	29.44	6.97
OC	1525.12	1503.41	1307.81	954.28	572.38	262.15	129.81	71.57	29.26	6.69
OD	1525.12	1503.41	1307.81	954.28	572.38	262.15	129.81	71.57	29.26	6.69



H[m]	D[m]	Max lux	Med lux	Alpha=30.2°+30.2°	G=0.0
1.00	1.16	1525	786		
2.00	2.33	381	196		
3.00	3.49	169	87		
4.00	4.65	95	49		
5.00	5.82	61	31		

H[m]	D[m]	Max lux	Med lux	Beta=30.2°+30.2°	G=0.0
1.00	1.16	1525	786		
2.00	2.33	381	196		
3.00	3.49	169	87		
4.00	4.65	95	49		
5.00	5.81	61	31		